

U.S. Department
of Transportation

800 Independence Ave., S.W.
Washington D.C. 20591

**Federal Aviation
Administration**

Transmittal Letter 20-09

March 6, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as
follows:

.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/23/2020	NJ	Trenton	Trenton Mercer	0/1232	3/3/2020	RNAV (GPS) RWY 16, Orig-B

AIRAC Date: 23 APRIL 2020

FDC 0/1232 TTN IAP TRENTON MERCER, TRENTON, NJ. RNAV (GPS) RWY 16, ORIG-B... CHART CIRCLING ICON.
CIRCLING CAT C MDA 760/HAA 547, CAT D MDA 960/747. CIRCLING CAT D VIS 2 1/2. ALTERNATE MINIMUMS:
STANDARD - CAT D 800-2 1/2. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USE
NORTHEAST PHILADELPHIA ALTIMETER SETTING; INCREASE LPV DA TO 510 FEET AND ALL CATS VISIBILITY 1/8
SM; LNAV/VNAV DA TO 576 FEET; INCREASE ALL MDA 60 FEET AND LNAV CAT C/D VISIBILITY 1/8 SM AND
CIRCLING CAT C VISIBILITY 1/4 SM. THIS IS RNAV (GPS) RWY 16, ORIG-C. 2002282039-PERM