

**ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	ILS: DA LOC: 6.14 NM AFTER GETTY INT OR AT I-CNL 1.34 DME
LIT VORTAC	GETTY INT/I-CNL 7.48 DME	250.79 / 6.55	2300	CLIMB TO 800 THEN CLIMBING RIGHT TURN TO 4000 ON HEADING 110 AND LIT VORTAC R-089 TO ATERS INT/LIT 16.00 DME AND HOLD. ALTERNATE MA (DO NOT CHART): CLIMB TO 800 THEN CLIMBING RIGHT TURN TO 4000 ON HEADING 110 AND PBF VOR/DME R-004 TO ATERS INT/PBF 24.82 DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 269.28 INBOUND. CHART FAS OBST: 512 TREE 344156N/0921520W. CHART LIT R-149 AT MOMTE. CHART CIRCLING ICON. CHART: ASR DO NOT CHART ALTERNATE MA HOLDING AT ATERS. CHART IN PLANVIEW: MYNIE OM SUBDUED. *LOC ONLY
MOMTE INT/LIT 12.00 DME CW (IAF)	BARBO/I-CNL 13.33 DME (NOPT)	12.00 DME ARC (LIT LR-227)	3500	
BARBO/I-CNL 13.33 DME (IF)	GETTY INT/I-CNL 7.48 DME	046.52 / 5.86	2300	

- PT L SIDE OF COURSE 226.52 OUTBOUND 2300 FT WITHIN 10 MILES OF GETTY INT (IAF)
-
- FAC: 046.52 FAF: GETTY INT/I-CNL 7.48 DME DIST FAF TO MAP: 6.14 THLD: 6.14
- MIN. ALT: GETTY 2300, OGRAY INT/I-CNL 3.11 DME 880*
- DIST TO THLD FROM OM: 6.14 MM: - IM: - 150 HAT: - 100 HAT: - GS ANT: 1000
- MIN GS INCPT: 2300 GS ALT AT: GETTY 2300 OM: - MM: - IM: -
- GS ANGLE: 3.00 TCH: 49.1
- MSA FROM: LIT VORTAC 3300

MAG VAR: 0E EPOCH YEAR: 2020

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	ILS: STANDARD	LOC: STANDARD @												
CATEGORY =====>	A		B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
S-ILS 04R	510	4000	250	510	4000	250	510	4000	250	510	4000	250			
S-LOC 04R	880	4000	620	880	4000	620	880	1 3/8	620	880	1 3/8	620			
CIRCLING	880	1	614	1000	1	734	1180	2 3/4	914	1180	3	914			

OGRAY (DUAL VOR RECEIVERS OR DME REQUIRED)

S-LOC 04R	780	4000	520	780	4000	520	780	5500	520	780	5500	520			
CIRCLING	820	1	554	1000	1	734	1180	2 3/4	914	1180	3	914			

NOTES:
 CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO S-ILS 4R.
 CHART NOTE: RWY 4R HELICOPTER VISIBILITY REDUCTION BELOW 3/4 NOT AUTHORIZED.
 CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED.
 CHART PROFILE NOTE: USE I-CNL DME WHEN ON THE LOCALIZER COURSE.

@ CAT C 1000-2 3/4, CAT D 1000-3



CITY AND STATE LITTLE ROCK, AR	ELEVATION: 266 TDZE: 260 AIRPORT NAME: BILL AND HILLARY CLINTON NATIONAL/ADAMS FIELD	FACILITY IDENTIFIER: I-CNL	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 4R, AMDT 2D 19 JULY 2018	SUP: AMDT: 2C DATED 05/29/2014
-----------------------------------	--	-------------------------------	--	--------------------------------------