

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KHDC	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 13	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> HAMMOND	<u>STATE</u> LA		
<u>AIRPORT ELEVATION</u> 46	<u>TDZE</u> 46	<u>SUPERSEDED</u>	<u>ORIGINAL/AMENDMENT</u> NONE	<u>DATED</u>	<u>MAG VAR</u> 0E	<u>EPOCH YEAR</u> 2010
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 20 APRIL 2023	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
HEVOT	IF	ZOPAD		TF	FB	1.00	134.43	6.00	1600
ZOPAD	FAF	ADAPE/2.75 NM RW13		TF	FB	0.30	134.48	1.54	
ADAPE/2.75 NM RW13		RW13	MAP	TF	FO	0.30	134.48	2.75	
RW13	MAP	440 MSL		CA			134.48		
440 MSL		COBIM		DF	FO	1.00			2000

MISSED APPROACH

MAP:

LNAV: RW13

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 2000 DIRECT COBIM AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

QUALITY
10
CHECKED

COORDINATED WITH:

A4A ☐ ALPA ☒ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZHU, NEW ORLEANS APP CON, ARPT MGR

FLIGHT CHECKED BY

MATTHEW OLSTAD

Digitally signed by
JASON KRETSCHMER
Feb 16, 2023

OFFICE

FPO

DATE

02/14/2023

DEVELOPED BY

ANDRE MARSH

Digitally signed by
JASON KRETSCHMER
Jan 13, 2023

OFFICE

AJV-A421

DATE

12/01/2022

APPROVED BY

MARLON ROBINSON

Digitally signed by
JASON KRETSCHMER
Jan 13, 2023

OFFICE

AJV-A420

DATE

TITLE
MANAGER

