

**Federal Aviation
Administration**

Transmittal Letter 20-11

April 3, 2020

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
5/21/2020	LA	Galliano	South Lafourche Leonard Miller Jr	0/1084	3/13/2020	RNAV (GPS) RWY 36, Amdt 1A

AIRAC Date: 21 MAY 2020

FDC 0/1084 GAO IAP SOUTH LAFOURCHE LEONARD MILLER JR, GALLIANO, LA. RNAV (GPS) RWY 36, AMDT 1A... DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: FOR INOP SSALR, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 3/4 MILE AND LNAV CAT C AND D VISIBILITY TO 1 MILE. CHART NOTE: FOR INOP ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 3/4 SM AND LNAV CAT C AND D VISIBILITY TO 1 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LOUIS ARMSTRONG NEW ORLEANS INTL ALTIMETER SETTING AND INCREASE ALL DA 77 FEET AND ALL MDA 80 FEET AND INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/8 MILE, LNAV CAT C AND D VISIBILITY 1/8 MILE AND CIRCLING CAT C AND D VISIBILITY 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LOUIS ARMSTRONG NEW ORLEANS INTL ALTIMETER SETTING AND INCREASE LPV DA TO 275 FEET, LNAV/VNAV DA TO 325 FEET AND ALL MDA 80 FEET AND INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/8 SM, LNAV CAT C AND D VISIBILITY 1/8 SM AND CIRCLING CAT C AND D VISIBILITY 1/4 SM. DELETE NOTE: FOR INOP SSALR, WHEN USING LOUIS ARMSTRONG NEW ORLEANS INTL ALTIMETER SETTING, INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 3/8 MILE. CHART NOTE: FOR INOP ALS, WHEN USING LOUIS ARMSTRONG NEW ORLEANS INTL ALTIMETER SETTING, INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 3/8 SM. DELETE PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE 3.00/TCH 39). DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. DELETE VDP AT *1 NM TO RW36. CHART VDP AT *.91 NM TO RW36. THIS IS RNAV (GPS) RWY 36, AMDT 1B.
2002041919-PERM