

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ROC VOR/DME (IAF)	POCZI INT (NOPT)	255.88 / 12.10	3000	ILS: DA LOC: 4.16 MILES AFTER TAVIA OM CLIMB TO 1500 THEN CLIMBING RIGHT TURN TO 3000 VIA HEADING 130 AND I-GVQ EAST COURSE TO POCZI INT AND HOLD; OR WHEN DIRECTED BY ATC, CLIMB TO 1500 THEN CLIMBING RIGHT TURN TO 3000 VIA HEADING 110 AND ROC R-256 TO POCZI INT/ROC 12.10 DME AND HOLD E, RT, 255.88 INBOUND. ADDITIONAL FLIGHT DATA: HOLD E, RT, 255.88 INBOUND. CHART: ALTERNATE MA HOLDING, HOLD E POCZI INT/ROC 12.10 DME, RT, 255.88 INBOUND. CHART FAS OBST: 990 ANTENNA 430144N/0780915W
GEE VOR/DME (IAF)	POCZI INT (NOPT)	333.83 / 14.28	3000	
POCZI INT (IF/IAF)	TAVIA OM	281.82 / 6.39	2400	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD E POCZI, RT, 281.82 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 281.82 FAF: TAVIA OM DIST FAF TO MAP: 4.16 THLD: 4.16
- MIN. ALT: POCZI 3000, TAVIA OM 2400
- DIST TO THLD FROM OM: 4.16 MM: 0.41 IM: - 150 HAT: - 100 HAT: - GS ANT: 1103
- MIN GS INCPT: 2400 GS ALT AT: GS INTCP OM: 2307 MM: 1098 IM: -
- GS ANGLE: 3.00 TCH: 56.2
- MSA FROM: ROC VOR/DME 090-270 3600, 270-090 2600

MAG VAR: 11W

EPOCH YEAR: 2000

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X											
CATEGORY >>>>>	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
S-ILS 28	1111	1/2	200	1111	1/2	200	1111	1/2	200	1111	1/2	200				
S-LOC 28	1260	1/2	349	1260	1/2	349	1260	1/2	349	1260	3/4	349				
CIRCLING	1380	1	467	1380	1	467	1380	1 1/2	467	1480	2	567				

NOTES:
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ROCHESTER ALTIMETER SETTING AND INCREASE ALL DA 102 FEET AND ALL MDA 120 FEET; INCREASE S-LOC 28 CATS C/D AND CIRCLING CAT D VISIBILITY 1/4 MILE. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON GEE VOR/DME AIRWAY RADIALS 287 CW 314 AND ROC VOR/DME AIRWAY RADIALS 264 CW 288.

CITY AND STATE BATAVIA, NY	ELEVATION: 913 TDZE: 911 AIRPORT NAME: GENESEE COUNTY	FACILITY IDENTIFIER: I-GVQ	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 28, AMDT 6 15 JAN 2009	SUP:
				AMDT: 5
				DATED 10/27/05

72 0901 Pub 01/15/09