FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE VOR STANDARD INSTRUMENT APPROACH PROCEDURE

TITLE 14 CFR PART 97.23

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.

Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPORT ID S12 PROCEDURE NAME ORIGINAL/AMENDMENT CITY STATE

VOR-A 5 ALBANY OR

 AIRPORT ELEVATION
 TDZE
 SUPERSEDED
 ORIGINAL/AMENDMENT
 DATED
 MAG VAR
 EPOCH YEAR

 227
 VOR/DME OR GPS-A
 4B
 06/17/2021
 18E
 1995

FACILITY COORDINATES OF FACILITIES ACTUAL EFFECTIVE DATE REQUIRED EFFECTIVE DATE CANCEL/SUSPEND

CVO

24 MARCH 2022

ROUTINE

COORDINATES OF FACILITIES

ACTUAL EFFECTIVE DATE

REQUIRED EFFECTIVE DATE

CANCELSUSPEND

24 MARCH 2022

TERMINAL ROUTES

FROM	FIX TYPE	<u>TO</u>	FIX TYPE	LEG TYPE	FO/FB	RNP	<u>COURSE</u>	DISTANCE	ALTITUDE
CVO VOR/DME	IF/IAF	SAIDY/6.90 DME					032.37	6.90	2500

MISSED APPROACH

MAP:

KINCI/12.34 DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1300 THEN CLIMBING LEFT TURN TO 3600 ON CVO VOR/DME R-032 TO CVO VOR/DME AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)

2. HOLD SW CVO VOR/DME, RT, 032.37 INBOUND, 3600 FT. IN LIEU OF PT (IAF), MAX 14000.

3. FAC: 032.37 **FAF:** SAIDY/6.90 DME **DIST FAF TO MAP: DIST FAF TO THLD:**

4. MIN ALT: CVO VOR/DME 3600, SAIDY/6.90 DME 2500

8. MSA FROM: CVO VOR/DME 5300

EQUIPMENT REQUIREMENTS NOTES:

DME REQUIRED.

NOTES:

CHART NOTE: RWY 16 AND 34 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON CVO VOR/DME AIRWAY RADIALS R-154 AND R-177. CHART NOTE: USE CORVALLIS ALTIMETER SETTING.



AIRPORT ID PROCEDURE NAME ORIGINAL/AMENDMENT CITY STATE
S12 VOR-A 5 ALBANY OR

ADDITIONAL FLIGHT DATA:

CHART CORVALLIS AWOS-3PT.

CHART FAS OBST: 508 TOWER (41-000083) 443651N/1230600W.

FAC CROSSES MIDPOINT OF RWY 16-34.

CHART CIRCLING ICON.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA

X

CATEGORY:	A		В		С			D			E				
FINAL TYPE	DA/MDA	<u>VIS</u>	HAT/HAA												
CIRCLING	940	1	713	1020	1	793		NA			NA				

CHANGES - REASONS

- 1. INCORPORATED CHANGES FROM P-NOTAM FOR AMDT 4A AND 4B INTO FORM IAW 8260.19I PARA 8-3-4 C (3).
- 2. CANCELS FDC NOTAM 1/5734 NIGHT LANDING AUTHORIZED RESTORED.
- 3. CHANGED PROCEDURE NAME FROM "VOR/DME OR GPS-A" TO "VOR-A" 8260.3E 1-6-3 B (1).
- 4. UPDATED ALL REFERENCES TO "CVO R-032.37/6.90 DME" IN TERMINAL ROUTES AND PROFILE TO "SAIDY/6.90 DME" ALL CNF FIXES REPLACED WITH NAVIGATIONAL FIX NAMES.
- 5. CHANGED MAP FROM "CVO R-032/12.30 DME" TO "KINCI/12.34 DME" FPT REQUESTED NEW LOCATION AND IAW 8260.19I PARA 8-6-6 C AND PARA 2-10-4 A (2).
- 6. AMENDED MISSED APPROACH INSTRUCTIONS FROM "CLIMBING LEFT TURN TO 3500 VIA CVO R-032 TO CVO VOR/DME AND HOLD" TO "CLIMB TO 1300 THEN CLIMBING LEFT TURN TO 3600 ON CVO VOR/DME R-032 TO CVO VOR/DME AND HOLD" PER FPT REQUEST AND THE INCREASE FROM 3500 TO 3600 REFERENCE 1500 OVER TERRAIN FOR AIRSPACE.
- 7. UPDATED PROFILE LINE 2 FROM "HOLD SW CVO VOR/DME, RT, 032.37 INBOUND, 3500 FT. IN LIEU OF PT (IAF)" TO "HOLD SW CVO VOR/DME, RT, 032.37 INBOUND, 3600 FT. IN LIEU OF PT (IAF), MAX 14000" NEW TARGETS EVALUATION AND IAW 8260.19I PARA 8-6-7 B (2).
- 8. DELETED LINE 3 DISTANCE FAF TO MAP "5.40" IAW 8260.19I PARA 8-6-7 C (3)
- 9. AMENDED PROFILE LINE 4 MIN ALTITUDE FROM "CVO VOR/DME 3500" TO "CVO VOR/DME 3600" NEW TARGETS AIRSPACE EVALUATION.
- 10. ADDED "CHART CIRCLING ICON" TO ADDITIONAL FLIGHT DATA 8260.19I 8-6-10.S.
- 11. UPDATED CHART PLANVIEW NOTE FROM "NOPT FOR ARRIVALS ON CVO VOR/DME AIRWAY RADIALS 154 CW 177" TO "NOPT FOR ARRIVAL ON CVO VOR/DME AIRWAY RADIALS R-154 AND R-177" IAW 8260.19I PARA 8-2-5 G (2).
- 12. DELETED ADDITIONAL FLIGHT DATA NOTE "HOLD SW, RT, 032 INBOUND" IAW 8260.19I PARA 8-6-6 G.
- 13. UPDATED ADDITIONAL FLIGHT DATA FROM "FAS OBST: 505 TOWER 443651/1230560" TO "CHART FAS OBST: 508 TOWER (41-000083) 443651N/1230600W" IAW 8260.19I PARA 8-6-10 C AND NEW CONTROLLING OBSTACLE.
- 14. ADDED ADDITIONAL FLIGHT DATA NOTE: "FAC CROSSES MIDPOINT OF RWY 16-34" IAW 8260.19I PARA 8-6-10 G (3).
- 15. UPDATED ALTERNATE MINIMUMS FROM, "ALTERNATE: # NA EXCEPT FOR OPERATIONS WITH APPROVED WEATHER SERVICE" TO "ALTERNATE: NA" IAW 8260.19I PARA 8-6-9 E AND 8260.3E PARA 3-4-1 A (1).
- 16. ADDED ADDITIONAL FLIGHT DATA NOTE: "CHART CORVALLIS AWOS-3PT" IAW 8260.19I PARA 8-2-4 B (3).
- 17. ADDED "CHART NOTE: RWY 16 AND 34 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED" IAW 8260.19I PARA 8-6-11 K (3).
- 18. ADDED "DME REQUIRED" TO EQUIPMENT REQUIREMENTS NOTES IAW 8260.19I PARA 8-6-8 A (2)(A).
- 19. REMOVED "OR WHEN DIRECTED BY ATC CLIMBING LEFT TURN TO 3000 VIA HEADING 125 AND EUG R-355 TO SHEDD INT AND HOLD N, RT, 175 INBOUND" PER FPT INSTRUCTION.

COORDINATED WITH:

NBAA X ALPA X AOPA X APA HAI I **OTHER:** EUG APCH, AMGR Digitally signed by **FLIGHT CHECKED BY ALLAN WILL OFFICE** DATE Nov 17, 2021 **FPO GARY J VEER** 11/10/2021 Digitally signed by **DEVELOPED BY OFFICE** DATE **ALLAN WILL** ALLAN WILL (DALLIN STRICKLAND) AJV-A423 08/17/2021 Digitally signed by **APPROVED BY OFFICE** DATE **ALLAN WILL** MARLON ROBINSON AJV-A420 Nov 17, 2021

TITLE

MANAGER