

**Federal Aviation
Administration**

Transmittal Letter 26-08

February 13, 2026

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
3/19/2026	MO	St Louis	Spirit Of St Louis	6/1850	1/12/2026	RNAV (GPS) RWY 8R, Orig-D

AIRAC Date: 19 MARCH 2026

FDC 6/1850 SUS IAP SPIRIT OF ST LOUIS, ST LOUIS, MO. RNAV (GPS) RWY 8R, ORIG-D...
CAT C CIRCLING MDA 1180/HAA 717. CHANGE NOTE TO READ: FOR UNCOMPENSATED
BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15 C OR ABOVE 54 C. BARO-VNAV AND
VDP NA WHEN USING STL ALTIMETER SETTING. WHEN LOCAL ALTIMETER SETTING NOT
RECEIVED, USE STL ALTIMETER SETTING AND INCREASE LPV DA TO 719 FEET,
INCREASE LNAV/VNAV DA TO 1186 FEET, INCREASE ALL MDA 60 FEET, INCREASE
VISIBILITY LNAV/VNAV ALL CATS AND LNAV CATS C/D 1/8 SM, AND CIRCLING CAT C 1/4
SM. FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 2 1/2 SM
AND LNAV CATS C/D VISIBILITY TO 1 5/8 SM. **RVR 1800 AUTHORIZED WITH USE OF FD
OR AP OR HUD TO DA, NA WHEN USING STL ALTIMETER SETTING. THIS IS RNAV (GPS)
RWY 8R, ORIG-E. 2601091707-PERM