

**Federal Aviation
Administration**

Transmittal Letter 24-13

April 26, 2024

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
6/13/2024	OH	Zanesville	Zanesville Muni	4/3168	4/8/2024	RNAV (GPS) RWY 4, Orig

AIRAC Date: 13 JUNE 2024

FDC 4/3168 ZZV IAP ZANESVILLE MUNI, ZANESVILLE, OH. RNAV (GPS) RWY 4, ORIG... LPV VISIBILITY 3/4 SM ALL CATS. LNAV/VNAV DA 1155/HAT 255 VISIBILITY 3/4 SM ALL CATS. LNAV MDA 1280/HAT 380. CIRCLING CAT B MDA 1420/ HAA 520. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -21 C OR ABOVE 54 C. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS. DELETE PROFILE NOTE: *LNAV ONLY. DELETE ASTERISK IN PROFILE VIEW FROM MINIMUM ALTITUDE AT GIRNS 1.8 NM TO RW04 1500 AND VDP AT 1 NM TO RW04. CHART NOTE: CIRCLING RWY 16, 34 NA AT NIGHT. DELETE NOTE: BARO-VNAV AND VDP NA WHEN USING NEWARK ALTIMETER SETTING. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE NEWARK ALTIMETER SETTING AND INCREASE ALL LPV AND LNAV/VNAV DA TO 1214 FEET AND ALL VISIBILITIES TO 1 SM, INCREASE ALL MDA 80 FEET; AND LNAV CAT C/D VISIBILITY 1/8 SM AND CIRCLING CAT C/D VISIBILITY 1/4 SM.. THIS IS RNAV (GPS) RWY 4, ORIG-A. 2403051735-PERM