

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> BAY BRIDGE	<u>AIRPORT ID</u> W29	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 29	<u>ORIGINAL/AMENDMENT</u> 1A	<u>CITY</u> STEVENSVILLE	<u>STATE</u> MD	
<u>AIRPORT ELEVATION</u> 15	<u>TDZE</u> 15	<u>SUPERSEDED</u> RNAV (GPS) RWY 29	<u>ORIGINAL/AMENDMENT</u> 1	<u>DATED</u> 01/05/2017	<u>MAG VAR</u> 11W	<u>EPOCH YEAR</u> 2000
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 26 MARCH 2020	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
AGARD	IAF	ZAKLY	NOPT	TF	FB	1.00	210.34	6.69	2100
ZAKLY	IF/IAF	AZLOM		TF	FB	1.00	293.98	5.15	1600
AZLOM	FAF	XITPY/2.20 NM TO RW29		TF	FB	0.30	293.93	2.65	
XITPY/2.20 NM TO RW29		RW29	MAP	TF	FO	0.30	293.93	2.20	
RW29	MAP	415 MSL		CA			293.93		
415 MSL		ZAKLY		DF	FO	1.00			2100

MISSED APPROACH

MAP:

LNAV: RW29

MISSED APPROACH INSTRUCTIONS:

CLIMBING RIGHT TURN TO 2100 DIRECT ZAKLY AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF (IAF)

2. HOLD SE ZAKLY, RT, 293.98 INBOUND, 2100 FT. IN LIEU OF PT (IAF), MAX 6000.

3. FAC: 293.93

FAF: AZLOM

DIST FAF TO MAP: 4.85

DIST FAF TO THLD: 4.85

4. MIN ALT: ZAKLY 2100, AZLOM 1600, XITPY/2.20 NM TO RW29 740

5. DIST TO THLD FROM OM:

MM:

IM:

150 HAT:

GS ANT:

6. MIN GP INCPT:

GP ALT AT FAF :

OM:

MM:

IM:

7. GP ANGLE:

34:1: IS NOT CLEAR

20:1: IS NOT CLEAR

TCH:

8. MSA FROM: RW29 2600

PBN REQUIREMENTS NOTE:

RNP APCH.

NOTES:

CHART NOTE: RWY 29 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT AGARD ON V44 EASTBOUND.

ADDITIONAL FLIGHT DATA:

CHART CIRCLING ICON.
CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES.
FAS OBST: 219 AAO 385740N/0761742W.
CHART 444 COMMUNICATION TWR 385802N/0761530W.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LNAV MDA	480	1	465	480	1	465		NA			NA				
CIRCLING	500	1	485	800	1	785		NA			NA				

CHANGES - REASONS

1. REMOVED STRAIGHT-IN AND CIRCLING AT NIGHT RESTRICTION - 20:1 PENETRATIONS LIGHTED
2. DELETED CHART NOTE: DME/DME RNP-0.3 NA NO LONGER REQUIRED.
3. REMOVED ALTIMETER NOTES FROM 8260-3 - ADDED TO 8260-9 PART C: GENERAL REMARKS FOR CONTINGENCY PURPOSES.
4. ADDED RNP APCH TO PBN REQUIRMENTS NOTE - IAW 8260.19H
5. ADDED MAX HOLDING 6000 AT ZAKLY - IAW 8260.19H PARA 8-6-7.B(2).



