U.S. Department of Transportation
Federal Aviation Administration

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
SBY VORTAC (40V)	CIRAN (TF) (FB) (40E) (41E) (43B)	144.01 / 17.86	2000
SWL VORTAC (IAF) (40V) (43A)	CIRAN (NoPT) (TF) (FB) (40E) (41E) (43B)	076.29 / 12.28	2000
CIRAN (IF/IAF) (40E) (40I)	BECAP (TF) (FB) (40E) (43F)	044.00 / 6.00	1600
RW02 (MAP) (40G) (41Y) (43M)	411 MSL (CA) (42M)	032.00	
411 MSL	CIRAN (DF) (FO) (40E) (41Y) (43H)		2000

MISSED APPROACH

LNAV: RW02

CLIMBING LEFT TURN TO 2000 DIRECT CIRAN AND HOLD.

ADDITIONAL FLIGHT DATA:

CHART FAS OBST: 95 TREE 381838N/0750747W

CHART: R-4006, W-386
CHART VDP AT 1.17 MILES TO RW02
BECAP TO RW02: 3.00 / 40

ROUTE TYPE DESCRIPTION: A, P
APPROACH ROUTE QUALIFIER 2: S

MAG VAR: 12W EPOCH YEAR: 00

1. PT ____ SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. HOLD SW CIRAN, LT, 044.00 INBOUND, 2000 FT. IN LIEU OF PT (IAF). (40E) (41E) (43C)
3. FAC: 032.00 FAF: BECAP DIST FAF TO MAP: 4.87 THLD: 4.87
4. MIN. ALT: CIRAN 2000, BECAP 1600
5. DIST TO THLD FROM OM: ____ MM: ____ IM: ____ 150 HAT: ____ 100 HAT: ____ GS ANT: ____
6. MIN GS INCPT: ____ GS ALT AT: ____ OM: ____ MM: ____ IM: ____
7. GS ANGLE: ____ TCH: 34:1 IS CLEAR
8. MSA FROM: RW02 2100

MINIMUMS

TAKEOFF: [ ] STANDARD [X] SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A [ ] STANDARD#

CATEGORY ==>	A			B			C			D			E		
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA	420	1	409	420	1	409	420	1 1/4	409						
CIRCLING	480	1	469	480	1	469	660	1 3/4	649						

NOTES: CHART NOTES:
DME/DME RNP-0.3 NA.
PROCEDURE NA AT NIGHT.
IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE SALISBURY ALTIMETER SETTING AND INCREASE ALL MDAs 60 FEET.

CHART PLAN VIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SWL VORTAC VIA V139 SOUTHWESTBOUND.
NA WHEN LOCAL WEATHER NOT AVAILABLE

CITY AND STATE	ELEVATION: 11 TDZE: 11 AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
OCEAN CITY, MD	OCEAN CITY MUNI	RNAV	SEP 1 2005 RNAV (GPS) RWY 2, ORIG	AMDT: NONE
				DATE