

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
UYOPI (IAF)	JISOD (NOPT) (FB)	083.89 / 5.00	3000	LPV: DA LNAV/VNAV: DA LNAV: RW35
CARIJ (IAF)	JISOD (NOPT) (FB)	264.01 / 5.00	3000	
JISOD (IF/IAF)	BIGOH (FB)	353.95 / 6.10	2800	CLIMB TO 3000 DIRECT FAVAN AND HOLD.
BIGOH (FAF)	IVICE/2.10 NM TO RW35 (FB)	353.95 / 3.12		
IVICE/2.10 NM TO RW35	RW35 (MAP) (FO)	353.95 / 2.10		
RW35 (MAP)	1317 MSL	353.95		ADDITIONAL FLIGHT DATA: HOLD N, RT, 173.94 INBOUND. CHART FAS OBST: 1196 SPIRE 352009N/0965548W CHART FAS OBST: 1269 TOWER 351938N/0965544W DISTANCE TO THLD FROM 250 HAT: 0.64 NM. WAAS CHANNEL # 72818 REFERENCE PATH ID: W35A LTP HAE: 297.7 M
1317 MSL	FAVAN (FO)		3000	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD S JISOD, RT, 353.95 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 353.95 FAF: BIGOH DIST FAF TO MAP: 5.22 THLD: 5.22
- MIN. ALT: JISOD 3000, BIGOH 2800, IVICE/2.10 NM TO RW35 1780*
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 2800 GS ALT AT: BIGOH 2800 OM: MM: IM:
- GS ANGLE: 3.00 TCH: 47.0 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 6E EPOCH YEAR: 2000

MINIMUMS															
TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT									ALTERNATE: N A			STANDARD @		
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1317	1	250	1317	1	250	1317	1	250						
LNAV/VNAV DA	1565	1 3/4	498	1565	1 3/4	498	1565	1 3/4	498						
LNAV MDA	1520	1	453	1520	1	453	1520	1 1/4	453						
CIRCLING	1600	1	527	1600	1	527	1600	1 1/2	527			NA			

NOTES:
 CHART NOTE: BARO-VNAV NA WHEN USING SEMINOLE ALTIMETER SETTING. @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 54C (130F).
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 (SEE FORM 8260-10)

CITY AND STATE SHAWNEE, OK	ELEVATION: 1073 TDZE: 1067 AIRPORT NAME: SHAWNEE RGNL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG-A 15 DEC 2011	SUP: AMDT: ORIG DATED 07/29/2010
-------------------------------	---	------------------------------	--	--

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

*LNAV ONLY

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SEMINOLE ALTIMETER SETTING AND INCREASE ALL DA/MDA 40 FEET. INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE.

TAA

	FROM	TO	ALT
1.	264/30 CW 084/30 (NOPT)	JISOD (IF/IAF) (FB)	3000
2.	084/30 CW 174/30	UYOPI (IAF) (FB)	3100
3.	174/30 CW 264/30	CARIJ (IAF) (FB)	3000

CITY AND STATE

SHAWNEE, OK

ELEVATION: 1073

TDZE: 1067

AIRPORT NAME:

SHAWNEE RGNL

FACILITY IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, ORIG-A

15 DEC 2011

SUP:

AMDT: ORIG

DATED: 07/29/2010

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KSNL
RUNWAY	RW35
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W35A
LTP/FTP LATITUDE	352100.6620N
LTP/FTP LONGITUDE	0965634.1750W
LTP/FTP ELLIPSOIDAL HEIGHT	+02977
FPAP LATITUDE	352229.9000N
FPAP LONGITUDE	0965634.2800W
THRESHOLD CROSSING HEIGHT (TCH)	00047.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1048
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER 43837899

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+03248
FPAP ORTHOMETRIC HEIGHT	+03248

CITY AND STATE SHAWNEE, OK	ELEVATION: 1073 TDZE: 1067	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG-A 15 DEC 2011	SUP:
	AIRPORT NAME: SHAWNEE RGNL			AMDT: ORIG
				DATED: 07/29/2010

