

U.S. Department of Transportation
Federal Aviation Administration

ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	ILS: AT THE DH.	LOC:										
UKW VORTAC	MUFIN LOM	143.52/44.61	4000	MUFIN	OR AT	1-FTW 1.49	DME FIX								
THIS IS A CORRECTED COPY OF A PROCEDURE PUBLISHED IN TL 06-03.				CLIMB TO 1300 THEN CLIMBING LEFT TURN TO 2500 DIRECT FT LOM AND HOLD, CONTINUE CLIMB-IN-HOLD TO 2500.											
				ADDITIONAL FLIGHT DATA: HOLD N, RT, 163.90 INBOUND CHART FAS OBST: 990 ELEVATOR 325155N/0972159W CHART VDP AT 2.98 DME; DISTANCE VDP TO THLD 1.49 MILES. CHART PLANVIEW NOTE: ADF REQUIRED.											
1. PT <u>R</u> SIDE OF COURSE <u>343.90</u> OUTBOUND <u>2400</u> FT WITHIN <u>10</u> MILES OF <u>MUFIN LOM</u> (IAF)															
2.															
3. FAC: <u>163.90</u> FAF: <u>MUFIN LOM-FTW 5.29 DME</u> DIST FAF TO MAP: <u>3.80</u> THLD: <u>3.80</u>															
4. MIN. ALT: <u>MUFIN 2000</u>															
5. DIST TO THLD FROM OM: <u>3.80</u> MM: <u></u> IM: <u></u> 150 HAT: <u></u> 100 HAT: <u></u> GS ANT: <u>1249</u>															
6. MIN GS INCPT: <u>2000</u> GS ALT AT: <u></u> OM: <u>1992</u> MM: <u>-</u> IM: <u>-</u>															
7. GS ANGLE: <u>3.00</u> TCH: <u>56.6</u>															
8. MSA FROM: <u>FT LOM 360-090 2200, 090-180 3600, 180-360 2800</u>				MAG VAR: <u>8E</u> EPOCH YEAR: <u>75</u>											
MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	ILS: STANDARD	LOC: STANDARD									
CATEGORY =====>	A			B			C	D	E						
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
S-ILS 16	910	2400	200	910	2400	200	910	2400	200	910	2400	200			
S-LOC 16	1240	2400	530	1240	2400	530	1240	5000	530	1240	6000	530			
CIRCLING	1260	1	550	1260	1	550	1280	1 1/2	570	1300	2	590			
NOTES:															
CITY AND STATE		ELEVATION: 710 TDZE: 710		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP:					
FORT WORTH, TX		AIRPORT NAME: FORT WORTH MEACHAM INTL		I-FTW		MAR 16 2006 ILS or LOC RWY 16, AMDT 8				AMDT: 7C					
										DATE 4/17/03					