

**Federal Aviation  
Administration**

**Transmittal Letter 22-21**

**August 19, 2022**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/6/2022	TN	Winchester	Winchester Muni	2/3176	8/5/2022	RNAV (GPS) RWY 36, Orig-C

**AIRAC Date: 6 OCTOBER 2022**

FDC 2/3176 BGF IAP WINCHESTER MUNI, WINCHESTER, TN. RNAV (GPS) RWY 36, ORIG-C... LNAV/VNAV VIS ALL CATS 1 1/8. DELETE PROFILE NOTE \*LNAV ONLY. CHART PROFILE NOTE: \*2260 WHEN USING CHATTANOOGA ALTIMETER SETTING. CHANGE VDP: \*1.4 NM TO RW36 TO READ 1.4 NM TO RW36. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER NOT RECEIVED, USE CHATTANOOGA ALTIMETER SETTING: INCREASE LPV DA TO 1483 FEET AND ALL VISIBILITIES 3/8 SM; INCREASE LNAV/VNAV DA TO 1510 FEET AND ALL VISIBILITIES 3/8 SM; INCREASE ALL MDAS 160 FEET AND LNAV VISIBILITY CAT C 3/8 SM AND CIRCLING CAT B/C 1/2 SM. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. DELETE NOTE: BARO-VNAV AND LNAV NA WHEN USING CHATTANOOGA ALTIMETER SETTING. DELETE NOTE: VDP NA WHEN USING CHATTANOOGA ALTIMETER SETTING. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING CHATTANOOGA ALTIMETER SETTING. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS. ALTERNATE MINIMUMS STANDARD: EXCEPT CAT B 900-2, CAT C 900-2 1/2; NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 36, ORIG-D. 2208031619-PERM