

**RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE
FBC VORTAC	KASPE (TF) (FO) (RNP 2.00)	159.54 / 9.37	3000
ROD VORTAC	COSOP (TF) (FB) (RNP 2.00)	033.43 / 20.93	3000
LAWTO (IAF)	KASPE (NOPT) (TF) (FB) (RNP 1.00)	292.00 / 8.65	2600
COSOP (IAF)	KASPE (NOPT) (TF) (FB) (RNP 1.00)	033.57 / 15.00	2600
KASPE (IF/IAF) (SEE FORM 8260-10)	FABKI (TF) (FB) (RNP 1.00)	005.32 / 6.09	2500

LPV: DA  
LNAV/VNAV: DA  
LNAV: RW36

CLIMB TO 2500 DIRECT GAVEY AND HOLD.

ADDITIONAL FLIGHT DATA:  
HOLD N, RT, 185.32 INBOUND.  
CHART FAS OBST: 949 TREE 405707N/0834102W.  
1064 AAO 405445N/0833939W.  
DISTANCE TO THLD FROM 297 HAT: 0.80 NM.  
CHART VDP AT 1.16 NM TO RW36\*  
\*LNAV ONLY.  
WAAS CHANNEL # 72705  
REFERENCE PATH ID: W36A  
LTP HAE: 209.4 M

MAG VAR: 5W                      EPOCH YEAR: 1985

1. PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
2. HOLD S KASPE, RT, 005.32 INBOUND, 2600 FT. IN LIEU OF PT (IAF)
3. FAC: 005.32 FAF: FABKI DIST FAF TO MAP: 5.11 THLD: 5.11
4. MIN. ALT: KASPE 2600, FABKI 2500
5. DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
6. MIN GS INCPT: 2500 GS ALT AT: FABKI 2500 OM:        MM:        IM:
7. GS ANGLE: 3.00 TCH: 46.7 20:1 IS CLEAR 34:1 IS CLEAR
8. MSA FROM: RW36 2900

**MINIMUMS**

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1106	1	297	1106	1	297	1106	1	297	1106	1	297			
LNAV/VNAV DA	1229	1 1/2	420	1229	1 1/2	420	1229	1 1/2	420	1229	1 1/2	420			
LNAV MDA	1220	1	411	1220	1	411	1220	1 1/4	411	1220	1 1/4	411			
CIRCLING	1440	1	627	1440	1	627	1440	1 3/4	627	1440	2	627			

NOTES:  
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 47C.  
CHART NOTE: BARO-VNAV AND VDP NA WHEN USING LIMA ALLEN COUNTY ALTIMETER SETTING.  
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).  
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LIMA ALLEN COUNTY ALTIMETER SETTING:  
(CONTINUED ON PAGE 2)



CITY AND STATE <b>FINDLAY, OH</b>	ELEVATION: 813      TDZE: 809 AIRPORT NAME: <b>FINDLAY</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 36, AMDT 1B</b> 24 MAY 2018	SUP: AMDT: <b>1A</b> DATED <b>11/18/2010</b>
--------------------------------------	--	-------------------------------------	--	--

**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
FABKI (FAF)	RW36 (MAP) (TF) (FO) (RNP 0.30)	005.32 / 5.10	
RW36 (MAP)	1106 MSL (CA)	005.32	
1106 MSL	GAVEY (DF) (FO) (RNP 1.00)		2500

**NOTES, (CONT.):**

INCREASE ALL DAS/MDAS 80 FEET; INCREASE LNAV CAT C/D VISIBILITY 1/8 SM AND CIRCLING CAT C/D VISIBILITY 1/4 SM.  
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON FBC VORTAC AIRWAY RADIALS 148 CW 200.  
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON ROD VORTAC AIRWAY RADIALS 023 CW 088.  
 PBN REQUIREMENTS NOTE: RNP APCH.



CITY AND STATE <b>FINDLAY, OH</b>	ELEVATION: 813 AIRPORT NAME: <b>FINDLAY</b>	TDZE: 809	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 36, AMDT 1B</b> 24 MAY 2018	SUP:
					AMDT: <b>1A</b>
					DATED: <b>11/18/2010</b>

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION**

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KFDY
RUNWAY	RW36
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W36A
LTP/FTP LATITUDE	410003.6380N
LTP/FTP LONGITUDE	0833958.5600W
LTP/FTP ELLIPSOIDAL HEIGHT	+02094
FPAP LATITUDE	410132.7890N
FPAP LONGITUDE	0833957.9235W
THRESHOLD CROSSING HEIGHT (TCH)	00046.7
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0768
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER 64FCEAE0

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02448
FPAP ORTHOMETRIC HEIGHT	+02448



CITY AND STATE FINDLAY, OH	ELEVATION: 813 TDZE: 809	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, AMDT 1B 24 MAY 2018	SUP:
	AIRPORT NAME: FINDLAY			AMDT: 1A
				DATED: 11/18/2010