

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> BPI	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 32	<u>ORIGINAL/AMENDMENT</u> 1A	<u>CITY</u> BIG PINEY	<u>STATE</u> WY
<u>AIRPORT ELEVATION</u> 6994	<u>TDZE</u> 6969	<u>SUPERSEDED</u> RNAV (GPS) RWY 31	<u>ORIGINAL/AMENDMENT</u> 1	<u>DATED</u> 06/15/2023
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 19 MARCH 2026	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>MAG VAR</u> 10E
				<u>EPOCH YEAR</u> 2030
				<u>CANCEL/SUSPEND</u>

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
GRIPS		OTAYI		TF	FB	1.00	357.95	29.31	9600
BPI VOR/DME		JITJU		TF	FO	1.00	133.18	10.21	9600
OTAYI	IAF	JITJU	NOPT	TF	FB	1.00	358.02	10.00	9000
JITJU	IF/IAF	HICDE		TF	FB	1.00	310.56	5.54	8400
HICDE	FAF	RW32	MAP	TF	FO	0.30	317.74	4.45	
RW32	MAP	7394 MSL		CA			317.74		
7394 MSL		JITJU		DF	FO	1.00			9000

MISSED APPROACH

MAP:

LNAV: RW32

MISSED APPROACH INSTRUCTIONS:

CLIMBING RIGHT TURN TO 9000 DIRECT JITJU AND HOLD

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2. HOLD SE JITJU, RT, 310.56 INBOUND, 9000 IN LIEU OF PT (IAF), MAX 14000.					
3. FAC: 317.74	FAF: HICDE		DIST FAF TO MAP: 4.45	DIST FAF TO THLD: 4.45	
4. MIN ALT: JITJU 9000, HICDE 8400					
5. DIST TO THLD FROM OM:	MM:	IM:	150 HAT:	GS ANT:	
6. MIN GP INCPT:	GP ALT AT FAF:			OM:	MM: IM:
7. GP ANGLE:	34:1: IS CLEAR	20:1: IS CLEAR	TCH:		
8. MSA FROM: RW32 12600					



PBN REQUIREMENTS NOTE:

RNP APCH - GPS.

NOTES:

CHART NOTE: CIRCLING NA TO RWYS 8 AND 26.

ADDITIONAL FLIGHT DATA:

CHART FAS OBST: 7141 TOWER (56-061641) 423333N/1100456W.
CHART VDP AT 1.50 NM TO RW32.
HICDE TO RW32: 3.00/32.5.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD - CAT C 900-2 1/4, CAT D 900-2 3/4, NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LNAV MDA	7460	1	491	7460	1	491	7460	1 3/8	491	7460	1 3/8	491			
CIRCLING	7460	1	466	7560	1	566	7800	2 1/4	806	7820	2 3/4	826			

CHANGES - REASONS

UPDATED ALL REFERENCES FROM "RWY 31" TO "RWY 32" – FPT REQUEST AND NOTAM BPI 06/003

COORDINATED WITH:

A4A ☐ ALPA ☒ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: SLC, AMGR

FLIGHT CHECKED BY

PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED 07/07/2021 GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION

OFFICE

DATE

Digitally signed by
ALLAN WILL
Aug 21, 2025

DEVELOPED BY

LIAM DONAHUE (ANA VEGA)

OFFICE

AJV-A412

DATE

07/29/2025

Digitally signed by
ALLAN WILL
Aug 21, 2025

APPROVED BY

KYLE THOMPSON

OFFICE

AJV-A33

DATE

Digitally signed by
ALLAN WILL
Aug 21, 2025

TITLE

MANAGER

