U.S. Department of Transportation

Federal Aviation Administration

Transmittal Letter 22-21

August 19, 2022

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/6/2022	ОН	Oxford	Miami University	2/6625	8/10/2022	RNAV (GPS) RWY 5, Orig-A

AIRAC Date: 6 OCTOBER 2022

FDC 2/6625 OXD IAP MIAMI UNIVERSITY, OXFORD, OH. RNAV (GPS) RWY 5, ORIG-A... CIRCLING CAT B MDA 1600/HAA 559. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS. DELETE NOTE: WHEN VGSI INOP, CIRCLING RWY 23 NA AT NIGHT. DELETE NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 5 PROCEDURE NA AT NIGHT. CHART NOTE: STRAIGHT-IN/CIRCLING RWY 5 AT NIGHT, OPERATIONAL VGSI REQUIRED, REMAIN ON OR ABOVE VGSI GLIDEPATH UNTIL THRESHOLD. CHANGE HELICOPTER NOTE TO READ: RWY 5 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. DELETE NOTE: *LNAV ONLY. DELETE ASTERISK FROM MINIMUM ALTITUDE AT UHOBI/1.60 NM TO RW05 1600. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE COVINGTON ALTIMETER SETTING: INCREASE LPV DA TO 1393 AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 1419 AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDA 100 FEET AND VISIBILITY LNAV CAT C 3/8 SM AND CIRCLING CAT C 1/4 SM. THIS IS RNAV (GPS) RWY 5, ORIG-B. 2208091901-PERM