U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
CQY VORTAC (IAF)	YATYU/13.00 DME (NOPT)	284.92 / 13.00	2400
YATYU/13.00 DME (IF)	WODIE/19.00 DME	284.92 / 6.00 (CQY R-285)	2100

MISSED APPROACH

MAP: WIVDU/CQY 24.06 DME FIX

CLIMBING RIGHT TURN TO 2400 ON CQY VORTAC R-285 TO WODIE/19.00 DME AND HOLD.

ADDITIONAL FLIGHT DATA:

CHART FAS OBST: 704 TANK 322020N/0963817W
CHART: 900 TOWER 321843N/0963708W
CHART: LANCASTER AWOS-3

1. PT ____ SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. HOLD E WODIE, RT, 284.92 INBOUND, 2400 FT. IN LIEU OF PT (IAF)
3. FAC 284.92 FAF WODIE/19.00 DME DIST FAF TO MAP ____ THLD ____
4. MIN. ALT WODIE 2100, ZOVUG/22.00 DME 1420
8. MSA FROM: CQY VORTAC 2400

MAG VAR: 6E EPOCH YEAR:1995

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: N A | X

CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
CIRCLING	1020	1	520	1040	1 1/4	540	1040	1 1/2	540		NA				

NOTES:

CHART NOTE: USE LANCASTER ALTIMETER SETTING; WHEN NOT RECEIVED, USE MID-WAY RGNL AND INCREASE ALL MDA 40 FEET.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON CQY VORTAC AIRWAY RADIALS 234 CW 263.

QUALITY CHECKED

CITY AND STATE	ELEVATION: 500 TDZE: AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP	
ENNIS, TX	ENNIS MUNI	CQY	5 MAY 2011 VOR/DME-A, AMDT 1	AMDT	ORIG-A
				DATE	02/16/2006

FAA FORM 8260-5 / April 2006 (computer generated)