

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE												
KUYRE (IF/IAF)	CAGNU (FB)	041.96 / 7.00	1500	LPV: DA LNAV/VNAV: DA LNAV: RW04 CLIMB TO 3000 DIRECT LURBY AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 222.13 INBOUND. CHART FAS OBST: 200 TWR 322958N/0920353W CHART: ASR. DISTANCE TO THLD FROM 200 HATH: 0.47 NM. WAAS CHANNEL # 56410 REFERENCE PATH ID: W04A LTP HAE: -2.9 M											
CAGNU (FAF)	UXGOY/1.30 NM TO RW04 (FB)	042.01 / 3.02													
UXGOY/1.30 NM TO RW04	RW04 (MAP) (FO)	042.03 / 1.30													
RW04 (MAP)	276 MSL	042.03													
276 MSL	LURBY (FO)		3000												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD SW KUYRE, RT, 041.96 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: 042.01 FAF: CAGNU DIST FAF TO MAP: 4.32 THLD: 4.32 4. MIN. ALT: KUYRE 2000, CAGNU 1500, UXGOY/1.30 NM TO RW04 540* 5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT: 6. MIN GS INCPT: 1500 GS ALT AT: CAGNU 1500 OM: MM: IM: 7. GS ANGLE: 3.00 TCH: 50.3 34:1 IS CLEAR 8. MSA FROM:				MAG VAR: 3E EPOCH YEAR: 1995											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD									
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	276	2400	200	276	2400	200	276	2400	200	276	2400	200			
LNAV/VNAV DA	381	2400	305	381	2400	305	381	2400	305	381	2400	305			
LNAV MDA	460	2400	384	460	2400	384	460	3500	384	460	3500	384			
CIRCLING	580	1	501	580	1	501	620	1 1/2	541	640	2	561			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. *LNAV ONLY															
CITY AND STATE		ELEVATION: 79 THRE: 76		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
MONROE, LA		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 4, AMDT 1				AMDT: ORIG					
		MONROE RGNL				15 NOVEMBER 2012				DATED 11/20/2008					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	312/30 CW 132/30 (NOPT)	312/10 CW 132/10	3100
2.	312/10 CW 132/10	KUYRE (IF/IAF) (FB)	2000
3.	132/30 CW 312/30	312/10 CW 312/10	3100
4.	132/10 CW 312/10	KUYRE (IF/IAF) (FO)	2000

CITY AND STATE
MONROE, LA

ELEVATION: 79 THRE: 76
AIRPORT NAME:
MONROE RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 4, AMDT 1
15 NOVEMBER 2012

SUP:
AMDT: ORIG
DATED: 11/20/2008

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KMLU
RUNWAY	RW04
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W04A
LTP/FTP LATITUDE	323013.8650N
LTP/FTP LONGITUDE	0920244.3480W
LTP/FTP ELLIPSOIDAL HEIGHT	-00029
FPAP LATITUDE	323116.9500N
FPAP LONGITUDE	0920129.7800W
THRESHOLD CROSSING HEIGHT (TCH)	00050.3
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0464
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

DA8CEDBA

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00230
FPAP ORTHOMETRIC HEIGHT	+00230

CITY AND STATE

MONROE, LA

ELEVATION: 79

THRE: 76

AIRPORT NAME:

MONROE RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 4, AMDT 1

15 NOVEMBER 2012

SUP:

AMDT: ORIG

DATED: 11/20/2008

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KMLUK4FR04	AKUYRE	010KUYREK4EA0EE	AR	HF		04200040		+ 02000	18000			A JS	
SUSAP KMLUK4FR04	R	010KUYREK4EA0E	I	IF				+ 02000	18000			A JS	
SUSAP KMLUK4FR04	R	020CAGNUK4EA1E	F	051TF		04200070		+ 01500				A JS	
SUSAP KMLUK4FR04	R	020CAGNUK4EA2WALPV			ALNAV/VNAV ALNAV							JS	
SUSAP KMLUK4FR04	R	021UXGOYK4EA0E	S	031TF		04200030		V 0054000540		-300		A JS	
SUSAP KMLUK4FR04	R	030RW04 K4PGOGY	M	031TF		04200013		00126		-300		A JS	
SUSAP KMLUK4FR04	R	040	0	M	CA	0420		+ 00276				A JS	
SUSAP KMLUK4FR04	R	050LURBYK4EA0EY		DF				+ 03000				A JS	
SUSAP KMLUK4FR04	R	060LURBYK4EA0EE	R	HM		22210040		+ 03000				A JS	

[illegible][illegible]

SUP:	
AMDT:	ORIG
DATED:	11/20/2008

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	KUYRE	KUYRE	010	IAF	HF	R	FO		042.0(045.0T)	004.0	AA 02000	
		KUYRE	010	FACF	IF		FB				AA 02000	
		CAGNU	020	FAF	TF		FB	0.5	042.0(045.0T)	007.0	AA 01500	
		UXGOY	021	SDF	TF		FB	0.3	042.0(045.0T)	003.0	AA 00540 GS 00540	
		RW04	030	MAP	TF		FO	0.3	042.0(045.0T)	001.3	AT 00126	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		042.0(045.0T)		AA 00276	
	LURBY	050		DF		FO				AA 03000	
	LURBY	060		HM	R	FO		222.1(225.1T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CAGNU	N322710.49	W0920620.87	N3227.175	W09206.348
	KUYRE	N322212.82	W0921211.59	N3222.214	W09212.193
	LURBY	N323932.92	W0915142.16	N3239.549	W09151.703
	UXGOY	N322918.64	W0920349.60	N3229.311	W09203.827
	RW04	N323013.87	W0920244.35	N3230.231	W09202.739

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW04	00076	50

CITY AND STATE
MONROE, LA

ELEVATION: 79 THRE: 76
 AIRPORT NAME:
 MONROE RGNL

FACILITY
 IDENTIFIER:
 RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
 RNAV (GPS) RWY 4, AMDT 1
 15 NOVEMBER 2012

SUP:
 AMDT: ORIG
 DATED: 11/20/2008