

**RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
WOXAV (IF/IAF)	HEPOP (FB)	268.00 / 6.30	2500	LNAV: RW27
HEPOP (FAF)	RW27 (MAP) (FO)	267.91 / 5.98		CLIMB TO 4400 DIRECT ZEBMU AND HOLD, CONTINUE CLIMB-IN-HOLD 4400.
RW27 (MAP)	959 MSL	267.91		
959 MSL	ZEBMU (FO)		4400	
				ADDITIONAL FLIGHT DATA: HOLD W, RT, 087.65 INBOUND. FAS OBST: 1239 AAO 405744N/0763226W 1339 AAO 405921N/0763105W CHART: PENN VALLEY ASOS HEPOP TO RW27: 3.00/40

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD E WOXAV, RT, 268.00 INBOUND, 4400 FT. IN LIEU OF PT (IAF)
- FAC: 267.91 FAF: HEPOP DIST FAF TO MAP: 5.98 THLD: 5.98
- MIN. ALT: HEPOP 2500
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 12W EPOCH YEAR: 2010

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1540	1 1/4	986	1540	1 1/2	986		NA			NA				
CIRCLING	1540	1 1/4	981	1620	1 1/2	1061		NA			NA				

NOTES:
 CHART NOTE: USE PENN VALLEY ALTIMETER SETTING; WHEN NOT RECEIVED, USE NORTHUMBLERLAND COUNTY ALTIMETER SETTING AND INCREASE ALL MDA 20 FT.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: PROCEDURE NA AT NIGHT.



CITY AND STATE DANVILLE, PA	ELEVATION: 559 THRE: 554 AIRPORT NAME: DANVILLE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 27, ORIG 31 MAY 2012	SUP: AMDT: NONE DATED
--------------------------------	--	------------------------------	--	-----------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	178/30 CW 358/30 (NOPT)	178/15 CW 358/15	5000
2.	178/15 CW 358/15	WOXAV (IF/IAF) (FB)	4400
3.	358/30 CW 178/30	WOXAV (IF/IAF) (FO)	4900

CITY AND STATE DANVILLE, PA	ELEVATION: 559	THRE: 554	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 27, ORIG 31 MAY 2012	SUP:
	AIRPORT NAME: DANVILLE				AMDT: NONE
					DATED:

