

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: RMG 27.21 DME FIX CLIMBING LEFT TURN TO 3000 VIA HEADING 240 AND RMG R-108 TO KAILA/21.00 DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD W, LT, 108.08 INBOUND. CHART FAS OBST: 1419 TREES 335922N/0843840W CHART 1919 TREES 335835N/0843446W. KAILA TO RW09: 2.93/40. CHART TDZE 1028							
RMG VORTAC (IAF)		TIPPY/11.00 DME		108.08 / 11.00				3000									
TIPPY/11.00 DME (IF)		KAILA/21.00 DME		108.08 / 10.00 (RMG R-108)				3000									
1. PT <u>NA</u> SIDE OF COURSE <u>OUTBOUND</u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT RMG VORTAC 3. FAC <u>108.08</u> FAF <u>KAILA/21.00 DME</u> DIST FAF TO MAP <u> </u> THLD <u>6.21</u> 4. MIN. ALT <u>RMG VORTAC 3000, TIPPY 3000, KAILA 3000</u> 8. MSA FROM: <u>RMG VORTAC 4200 (30 NM)</u>										MAG VAR: 1E		EPOCH YEAR: 1965					
MINIMUMS																	
TAKEOFF: <u> </u>		STANDARD <input checked="" type="checkbox"/>		SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A <input checked="" type="checkbox"/>									
CATEGORY =====>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-9	1900	1	872	1900	1 1/4	872	1900	2 1/2	872	1900	2 3/4	872					
CIRCLING	1900	1	860	1900	1 1/4	860	1900	2 1/2	860	2220	3	1180					
NOTES: CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HARTSFIELD-JACKSON ATLANTA INTL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND S-9 CAT A/C/D AND CIRCLING CAT A/C SEE 8260-10																	
CITY AND STATE ATLANTA, GA				ELEVATION: 1040 TDZE: 1028 AIRPORT NAME: COBB COUNTY-MC COLLUM FIELD				FACILITY IDENTIFIER: RMG		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 9, AMDT 2 12 MAR 2009				SUP AMDT 1A DATE 09/28/2006			

VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

VISIBILITIES 1/4 MILE.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT RMG VORTAC ON AIRWAY RADIALS 059 CW 165.

CITY AND STATE ATLANTA, GA	ELEVATION: 1040 TDZE: 1028 AIRPORT NAME: COBB COUNTY-MC COLLUM FIELD	FACILITY IDENTIFIER: RMG	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 9, AMDT 2 12 MAR 2009	SUP:
				AMDT: 1A
				DATED: 09/28/2006