


TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ELX VOR/DME	KIMBY (FB)	114.35 / 12.24	2700	LNAV: RW27
LINGS	ZUDOB (FB)	019.68 / 3.52	2700	
RESGY (IAF)	YEGTU (NOPT) (FB)	244.98 / 14.44	2700	CLIMB TO 2500 DIRECT JUBLA AND HOLD.
KIMBY (IAF)	YEGTU (NOPT) (FB)	185.25 / 5.00	2700	
ZUDOB (IAF)	YEGTU (NOPT) (FB)	005.25 / 5.00	2700	
YEGTU (IF/IAF)	WUKOV (FB)	275.25 / 6.18	2500	
				ADDITIONAL FLIGHT DATA: HOLD W, RT, 094.90 INBOUND. CHART FAS OBST: 999 TREE 415959N/0860334W WUKOV TO RW27: 3.04/35.

1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
2. HOLD E YEGTU, RT, 275.25 INBOUND, 2700 FT. IN LIEU OF PT (IAF)
3. FAC: 275.16 FAF: WUKOV DIST FAF TO MAP: 5.32 THLD: 5.32
4. MIN. ALT: YEGTU 2700, WUKOV 2500, SLOAT/2.50 NM TO RW27 1580
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR
8. MSA FROM: RW27 3000

MAG VAR: 5W EPOCH YEAR: 2010

MINIMUMS																
TAKEOFF:	STANDARD	<input checked="" type="checkbox"/>	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N	<input checked="" type="checkbox"/>											
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA	1260	1	513	1260	1	513	1260	1 1/2	513	1260	1 3/4	513				
CIRCLING	1320	1	573	1320	1	573	1340	1 1/2	593	1340	2	593				

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: PROCEDURE NA AT NIGHT.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF, WHEN NOT RECEIVED, USE ELKHART ALTIMETER
 SEE 8260-10



CITY AND STATE DOWAGIAC, MI	ELEVATION: 747 TDZE: 747 AIRPORT NAME: DOWAGIAC MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 27, ORIG 29 JUL 2010	SUP: AMDT: NONE DATED
--------------------------------	--	------------------------------	--	-----------------------------

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

SETTING AND INCREASE ALL MDA 60 FEET; INCREASE CIRCLING CAT C VISIBILITY 1/4 MILE.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON ELX VOR/DME AIRWAY RADIALS 061 CW 077.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT RESGY ON V285 NORTHBOUND.



CITY AND STATE DOWAGIAC, MI	ELEVATION: 747 TDZE: 747 AIRPORT NAME: DOWAGIAC MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 27, ORIG 29 JUL 2010	SUP:
				AMDT: NONE
				DATED:

