

# EL DORADO NINE DEPARTURE

ASOS  
119.925  
CLNC DEL  
125.2  
CTAF  
123.0  
HOUSTON DEP CON  
134.45 284.0

**TOP ALTITUDE:  
ASSIGNED BY ATC**

EL DORADO  
115.5 ELD  
Chan 102  
N33°15.37'-W92°44.64'  
L-17, H-6

NOTE: RADAR required.  
NOTE: For aircraft destined MEM  
or filed via Q32 or J42.

LUFKIN  
112.1 LFK  
Chan 58

ENJOY  
N31°16.73'  
W94°19.82'

MUSIQ  
N30°33.17'  
W94°53.53'

VELCO  
N31°10.67'  
W94°24.55'  
10000

DARTR  
N30°24.19'  
W95°00.41'

RAECN  
N30°05.08'  
W95°14.95'

DAISETTA  
116.9 DAS  
Chan 116

HUMBLE  
116.6 IAH  
Chan 113

**TAKEOFF MINIMUMS**  
Rwys 17, 35: Standard.

NOTE: Chart not to scale.

## DEPARTURE ROUTE DESCRIPTION

TAKEOFF ALL RWYS: When entering controlled airspace, climb on assigned heading for RADAR vectors to RAECN INT. Maintain ATC assigned altitude. Expect filed altitude 10 minutes after departure, thence. . . .

. . . .on IAH R-028 and the ELD R-208 to ELD VOR/DME, cross VELCO INT at or above 10000.