

LOC/DME I-ATL 109.9 Chan 36	APP CRS 095°	Rwy Idg 8R 9999 8800 8L 1024 1015 TDZE Apt Elev 1026 1026
---	------------------------	--

ILS or LOC RWY 8R


HARTSFIELD-JACKSON ATLANTA INTL (ATL)

▼ Inop table does not apply to Sidestep 8L Cats A and B. For inop ALSF-2, increase Sidestep 8L Cat E visibility to 2. Simultaneous approach authorized with Rwy 9L or 9R or 10. ADF or DME or RADAR required.


Rwy 8L ALSF-2

MISSED APPROACH: Climb to 1500 then climbing left turn to 3500 on ATL VORTAC R-005 to TROYS INT/ATL 15 DME and hold. (TACAN aircraft climb to 1500 then climbing left turn to 3500 on heading 005° for RADAR vectors.)

D-ATIS ARR 119.65	ATLANTA APP CON DEP 127.9 379.9	ATLANTA TOWER 8L-26R 119.1 8R-26L 125.325 9L-27R 123.85 9R-27L 119.3	ALL RWYS 10-28 119.5 254.4	GND CON (8L-26R,8R-26L) 121.9 (9L-27R,9R-27L) 121.75	ALL RWYS 10-28 121.65 254.4
-----------------------------	---	---	--------------------------------------	---	---------------------------------------




RADAR REQUIRED



ELEV 1026	TDZE 8R 1024	TDZE 8L 1015
-----------	--------------	--------------

CATEGORY	A	B	C	D	E
S-ILS 8R	1278/40		254 (300-¾)		
S-LOC 8R	1440/55	416 (500-1)	1440/60		416 (500-1½)
SIDESTEP 8L	1440/55		425 (500-1)	1440-1½	
			425 (500-1½)		



HIREL all Rwys TDZ/CL Rwys 8L, 9R, 10, 26R, 27L and 28					
FAF to MAP 5.4 NM					
Knots	60	90	120	150	180
Min:Sec	5:24	3:36	2:42	2:10	1:48

SE-4, 10 OCT 2019 to 07 NOV 2019

SE-4, 10 OCT 2019 to 07 NOV 2019