ILS or LOC RWY 5L

RALEIGH-DURHAM INTL (RDU)

LOC/DME I-GKK	APP CRS	Rwy Idg 10000
109.1	054°	TDZE 384
Chan 28		Apt Elev 435

RADAR required for procedure entry, DME required.

Simultaneous approach authorized.

MALSR

MISSED APPROACH: Climb to 1000 then climbing left turn to 2200 on heading 310° and RDU VORTAC R-356 to DUHAM INT/RDU 11 DME and hold.

D-ATIS	RALEIGH APP CON	(EAST) RALEIGH TOWER (WEST)		(EAST) GND CON (WEST)		CLNC DEL	CPDLC
123.8	128.3 307.9	127.45 257.8 Rwys 5R-23L and 14-32	119.3 257.8 Rwy 5L-23R	121.9 348.6 Rwys 5R-23L and 14-32	121.7 348.6 Rwy 5L-23R	120.1	







CATEGORY	A	B	C	D
S-ILS 5L	595/18 211 (200-½)			
S-LOC 5L	880/24 496 (500-½)		880/40 496 (500-¾)	880/50 496 (500-1)
C CIRCLING	960-1 525 (600-1)		1040-1¾ 605 (700-1¾)	1180-2½ 745 (800-2½)

FAF to MAP 5.2 NM

Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

SE-2, 10 OCT 2019 to 07 NOV 2019