RNAV (GPS) Y RWY 2C

NASHVILLE INTL (BNA)

WAAS	APP CRS	Rwy Idg	7601
CH 70613	021°	TDZE	587
W02B		Apt Elev	599

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above 54°C (130°F). Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations. Simultaneous approach authorized with Rwy 2R. DME/DME RNP-0.3 NA.
** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 4000 direct GUYEK and on track 019° to HIKRY and hold, continue climb-in-hold to 4000.

D-ATIS	NASHVILLE APP CON	NASHVILLE TOWER	GND CON	CLNC DEL	CPDLC
135.1	118.4 360.7	118.6 257.8	121.9 348.6	126.05	





CATEGORY	A	B	C	D
LPV DA**	787/24 200 (200-½)			
LNAV/VNAV DA	1059/60 472 (500-1¼)			
LNAV MDA	1000/24 413 (500-½)		1000/40 413 (500-¾)	
C CIRCLING	1100-1 501 (600-1)	1120-1 521 (600-1)	1200-1¾ 601 (700-1¾)	1380-2½ 781 (800-2½)

ELEV 599 D TDZE 587



SE-1, 16 JUL 2020 to 13 AUG 2020
SE-1, 16 JUL 2020 to 13 AUG 2020