

**TOP ALTITUDE:
ASSIGNED BY ATC**

ATIS
127.55
CLNC DEL
126.6 239.0
CPDLC
GND CON
121.7
SOCAL DEP CON
134.2 338.2

R-086

11000
*3700
266°
(25)

COREZ
N35°33.40'
W119°29.03'

AVENAL
117.1 AVE
Chan 118
N35°38.82'-W119°58.72'
L-3-7, H-4

R-147

11000
*3800
310°
(55)

GORMAN
116.1 GMN
Chan 108
N34°48.24'-W118°51.68'
L-3-4-7, H-4

R-021

9500
322°
(18)

CASTA
N34°31.97'
W118°43.60'
8300

R-120

5000
300°
(11)

FILLMORE
112.5 FIM
Chan 72
N34°21.40'-W118°52.88'
L-3-4-7, H-4


R-255

5000
*4000
255°
(7)

SUANA
N34°13.39'
W118°43.24'

IPIHO
N34°13.40'
W118°34.44'

VAN NUYS
113.1 VNY
Chan 78



NOTE: RADAR required.
NOTE: For all Rws: Do not intercept any departure radial until advised by ATC.
NOTE: DME required.
NOTE: Cross VNY DME 1.5 DME south at or below 1750.

TAKEOFF MINIMUMS

- Rwy 16L: Standard with minimum climb of 380' per NM to 8300. Fillmore Transition standard with minimum climb of 380' per NM to 5000.
- Rwy 16R: Standard with minimum climb of 450' per NM to 8300. Fillmore Transition standard with minimum climb of 450' per NM to 5000.
- Rwy 34L/R: Standard with minimum climb of 370' per NM to 8300. Fillmore Transition standard with minimum climb of 370' per NM to 5000.

NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)

SW-3, 16 JUL 2020 to 13 AUG 2020

SW-3, 16 JUL 2020 to 13 AUG 2020