

METRO TWO DEPARTURE

AL-467 (FAA)

WILLOW RUN (YIP)

DETROIT, MICHIGAN

**TOP ALTITUDE:
3000**



PISTN
N42°53.54'
W83°08.19'
L-28

DUNKS
N42°25.64'
W84°11.65'
L-28, H-10

HARWL
N42°15.84'
W84°11.65'
L-28

MAARS
N42°05.30'
W82°29.17'
L-30

DETROIT
113.4 DXO
Chan 81
N42°12.79'-W83°22.00'
L-28, H-10

ANNTS
N41°41.01'
W83°47.44'
L-28

ILLIE
N41°14.91'
W84°07.96'
L-28

TAKEOFF MINIMUMS

Rwys 5L/R, 9, 23L/R: Standard.

Rwy 27: 300-1½ or standard with a minimum climb of 206' per NM to 1000, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 1300' prior to departure end of runway.

ATIS 127.425
GND CON
119.975
WILLOW RUN TOWER
125.275 256.9
DETROIT DEP CON
118.95 284.0

- NOTE: RADAR required.
- NOTE: DME required.
- NOTE: For use by non-RNAV equipped aircraft only.

SPECIAL INSTRUCTIONS:

When using this departure, file the appropriate depicted departure fix and route. Aircraft over HARWL must file FL220 and below. PROP AIRCRAFT departing Rwy 21L/R and 22L/R westbound, cross DXO 3.5 DME at or above 2500 MSL. Aircraft landing Cleveland (CLE) must file via MAARS. Turbojet departures at/above 10000, maintain 280K until advised by ATC. If unable, advise ATC prior to departure.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

METRO TWO DEPARTURE

DETROIT, MICHIGAN

WILLOW RUN (YIP)