RNAV (RNP) Z RWY 31L

DALLAS-FORT WORTH INTL (DFW)

APP CRS	Rwy Idg	9300
315°	TDZE	581
	Apt Elev	607

For uncompensated Baro-VNAV systems, procedure NA below -4°C (25°F) or above 54°C (130°F). Simultaneous approach authorized with Rwy 31R. GPS Required. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MISSED APPROACH: Climb to 3000 on track 315° to HODAX and on track 306° to KAGLE and hold.

D-ATIS	REGIONAL APP CON	DFW TOWER	GND CON	CLNC DEL	CPDLC
ARR 123.775 DEP 135.925	118.425 127.075 119.4	126.55 127.5 EAST 124.15 134.9 WEST	121.65 121.8 EAST 121.85 WEST	128.25	



ELEV 607 | D | TDZE 581



HIRL all Rwys
REIL Rwys 13L and 31L
TDZ/CL all Rwys except 13L and 31L

3000 tr 315°	HODAX	tr 306°	KAGLE

VGSI and RNAV glidepath not coincident (VGSI Angle 3.13/TCH 72).



CATEGORY	A	B	C	D
RNP 0.30 DA	951/60	370 (400-1¼)		

AUTHORIZATION REQUIRED

SC-2, 08 OCT 2020 to 05 NOV 2020
SC-2, 08 OCT 2020 to 05 NOV 2020