ILS or LOC RWY 36R

CHARLOTTE/DOUGLAS INTL (CLT)

LOC/DME I-BQC	APP CRS	Rwy Idg	8390
108.9	003°	TDZE	727
Chan 26		Apt Elev	748

Circling NA at night. Simultaneous approach authorized. DME or RADAR required.

ALSF-2

MISSED APPROACH: Climb to 1320 then climbing right turn to 4000 on CLT VOR/DME R-093 to LOCAS INT/24.9 DME and hold.

D-ATIS	CHARLOTTE APP CON		CHARLOTTE TOWER			GND CON	CLNC DEL
ARR 121.15	(001°-119°)	128.32	(Rwys 18L-36R, 5-23)	118.1	257.8	121.8 348.6 (WEST)	127.15
DEP 132.1	(120°-295°)	120.05	(Rwy 18C-36C)	126.4	257.8	121.9 348.6 (EAST)	348.6
	(296°-360°)	134.75	(Rwy 18R-36L)	133.35	257.8		CPDLC
	(180°-359°)	257.2					
	(360°-179°)	307.8					



RADAR REQUIRED

ELEV 748 D TDZE 727

HIRL all Rwys
REIL Rwys 18L and 23
TDZ/CL Rwys 18R, 36L, 36C and 36R



FAF to MAP 5.4 NM

Knots	60	90	120	150	180
Min:Sec	5:24	3:36	2:42	2:10	1:48

1320	4000	CLT R-093	LOCAS CLT 24.9

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 74).



CATEGORY	A	B	C	D
S-ILS 36R	927/18 200 (200-½)			
S-LOC 36R	1120/24 393 (400-½)		1120/35 393 (400-⅝)	
C CIRCLING	1380-1 632 (700-1)		1500-2¼ 752 (800-2¼)	1500-2½ 752 (800-2½)

SE-2, 25 MAR 2021 to 22 APR 2021
SE-2, 25 MAR 2021 to 22 APR 2021