

NE-4, 25 MAR 2021 to 22 APR 2021

ASOS 119.925
CLNC DEL
121.8 257.65
132.075 269.075 (When Tower Closed)
GNID CON
121.8 257.65
MARTINSBURG TOWER *
124.3 (CTAF) 233.7
POTOMAC DEP CON
126.825 239.025


DEPARTURE ROUTE DESCRIPTION

Climb on heading assigned by ATC, expect RADAR vectors to POOCH, then on track 240° to SCRAM, thence

. . . . as depicted. Maintain 3000, expect clearance to filed altitude within ten (10) minutes after departure.

GLANC TRANSITION (SCRAM6.GLANC):

TOP ALTITUDE:
3000



TAKEOFF MINIMUMS

Rwy 8: Standard.
Rwy 26: Standard with a minimum climb of 225' per NM to 2100.

NOTE: RNAV 1.

NOTE: RADAR required.

NOTE: DME/DME/IRU or GPS required.

NOTE: Turbo-jets only.

NOTE: Takeoff Rwy 8, if issued an ATC heading that requires a westbound turn, climb heading 081° to 1200 prior to turning for obstacle avoidance.

NOTE: Takeoff Rwy 26, if issued an ATC heading that requires a right turn, climb heading 261° to 2400 prior to turning for obstacle avoidance.

POOCH
3000



NOTE: Chart not to scale.

NE-4, 25 MAR 2021 to 22 APR 2021