ILS Y or LOC Y RWY 19

JACKSON HOLE (JAC)

LOC/DME I-JAC	APP CRS	Rwy Idg	6300
109.1	187°	TDZE	6451
Chan 28		Apt Elev	6451

RADAR required for procedure entry at MOSSS.

Circling NA for Cats A, B and C east of Rwy 1-19. Circling NA for Cat D. For inop ALS, increase SOSUE fix minimums S-LOC 19 Cats C and D visibility to 2½ SM. For inop ALS, increase S-LOC Cat C and D visibility to 3 SM.

-22°C

MALS

MISSED APPROACH: Climb to 14000 on JAC VOR/DME R-192 to KICNE INT/JAC VOR/DME 26.6 DME and hold, continue climb-in-hold to 14000.

D-ATIS	SALT LAKE CENTER	JACKSON TOWER ★	GND CON	UNICOM
120.625	133.25 285.6	118.075 (CTAF) L	124.55	122.95



ELEV 6451	D	TDZE 6451



FAF to MAP 9.7 NM

Knots	60	90	120	150	180
Min:Sec	9:42	6:28	4:51	3:53	3:14



CATEGORY	A	B	C	D
S-ILS 19	7077-1½ 626 (700-1½)			
S-LOC 19	7540/55 1089 (1100-1)	7540-1¼ 1089 (1100-1¼)	7540-2½ 1089 (1100-2½)	
C CIRCLING	7540-1¼ 1089 (1100-1¼)	7540-1½ 1089 (1100-1½)	7540-3 1089 (1100-3)	NA
SOSUE FIX MINIMUMS (DME REQUIRED)				
S-LOC 19	7300/40 849 (900-¾)	7300/55 849 (900-1)	7300-2 849 (900-2)	
C CIRCLING	7300-1¼ 849 (900-1¼)		7400-2¾ 949 (1000-2¾)	NA

NW-1, 13 JUN 2024 to 11 JUL 2024
NW-1, 13 JUN 2024 to 11 JUL 2024