CORPUS CHRISTI, TEXAS

RNAV (GPS) RWY 36

APCH CRS	Rwy ldg	5002
357°	TDZE	18
	Arpt Elev	18

[USN] CORPUS CHRISTI NAS (TRUAX FLD) (KNGP)

RNP APCH

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15° C (5° F) or above 54° C (129° F).

MISSED APPROACH: Climb to 600, then climbing right turn to 2000 direct FOLEM and hold.

ATIS ★	APP CON	NAVY CORPUS TOWER ★	GND CON	CLNC DEL	ASR/PAR
127.9 290.9	128.675 343.75	134.85 (L) 340.2	118.7 257.85	314.3	

105

CORPUS CHRISTI CRP

4 NM

042° 230K 222°

HOLD 6000 2000

FOLEM

2000 158° (25.3)

1068

Baro-VNAV NA when local altimeter not available.

Northbound arrivals on V70-407 and V13-20-163 require turn in holding at CRP VORTAC (See L-20), or RADAR vectors. Holding at CRP NA for TACAN users.

When local altimeter setting not received, use Corpus Christi (CRP) Intl altimeter setting.

279 158 RW36 143 201

(FAF) MUGVE

1600 (6) 357°

(IF/IAF) TYSON

83 177° 28 230K 357°

HOLD 6000 2000

4 NM

EMERG SAFE ALT 100 NM 11,100

MSA RW36 25 NM 2100

600 2000 FOLEM

VDP NA when using Corpus Christi (CRP) Intl altimeter setting.

4 NM Holding Pattern

TYSON 177° 6000 2000

MUGVE 357° 357° 2000

1 NM to RW36

RW36

1600

GP 3.00° TCH 50

4.8 NM

ELEV 18 TDZE 18

HIRL Rwy 4-22, 13R-31L (L)
HIRL Rwy 13L-31R, 18-36
REIL Rwy 4-22, 13L-31R, 18-36, 31L



CATEGORY	A	B	C	D
LNAV MDA	400-1 382 (400-1)		400-1⅛ 382 (400-1⅛)	
LNAV/VNAV DA	400-1⅛ 382 (400-1⅛)			
C CIRCLING	460-1 442 (500-1)	480-1 462 (500-1)	520-1½ 502 (600-1½)	580-2 562 (600-2)
CORPUS CHRISTI (CRP) INTL ALTIMETER SETTING				
LNAV MDA	440-1 422 (500-1)		440-1¼ 422 (500-1¼)	
C CIRCLING	500-1 482 (500-1)		540-1½ 522 (600-1½)	620-2 602 (700-2)

CORPUS CHRISTI, TEXAS

Amdt 2 30NOV23

27°42'N-97°17'W CORPUS CHRISTI NAS (TRUAX FLD) (KNGP)

RNAV (GPS) RWY 36

SC-3, 11 JUL 2024 to 08 AUG 2024