

**TOP ALTITUDE:
ASSIGNED BY ATC**

D-ATIS	120.0	254.3
CLNC DEL	125.0	379.1
GND CON	121.9	348.6
EL PASO TOWER	118.3	239.275
EL PASO DEP CON	119.15	263.0
ALBUQUERQUE CENTER	122.4	122.55

GREBE ▲


SLNNK ✧

FL180 *9800
004° (23)
BOATY ✧

FL180 *12400
304° (85)
FL180 *9800
321° (47)

TAKEOFF MINIMUMS

Rwy 4: Standard with minimum climb of 500' per NM to 12400.



RUTER ▲

17900
*7200
303° (19)

HBACK ✧

FL180 *17000
265° (110)
TELKE ✧

FL180 *17000
271° (109)
R-5115

SNTRS 14000 ✧

14000
*9400
305° (111)
JCOXX ✧
263°
13000
*9400 (8)

MRGEZ 13000 ✧

6450

042°

- NOTE: Takeoff Rwy 4, do not exceed 230K until passing 6450.
- NOTE: For use by Turbojet aircraft only.
- NOTE: RADAR required for non-GPS equipped aircraft.
- NOTE: DME/DME/IRU or GPS required.
- NOTE: RNAV 1.

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 4: Climb heading 042° to 6450, then left turn direct JCOXX, thence. . .
 . . .(transition). Maintain altitude as assigned by ATC, expect filed altitude 10 minutes after departure.

- GREBE TRANSITION (JCOXX2.GREBE)
- HBACK TRANSITION (JCOXX2.HBACK)
- SLNNK TRANSITION (JCOXX2.SLNNK)
- TELKE TRANSITION (JCOXX2.TELKE)