

WAAS CH <b>90327</b> <b>W32A</b>	APP CRS <b>315°</b>	Rwy Idg TDZE Apt Elev	<b>5006</b> <b>665</b> <b>678</b>
--	------------------------	-----------------------------	---




# RNAV (GPS) RWY 32

CHEROKEE COUNTY (JSO)

**⚠** Baro-VNAV NA when using Nacogdoches altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). When local altimeter setting not received, use Nacogdoches altimeter setting and increase DA 118 feet, increase all MDA 120 feet and LPV, LNAV/VNAV visibility all Cats ¼ mile, LNAV and Circling Cat C visibility ⅜ mile. When VGSi inop, Straight-in/Circling Rwy 32 procedure NA at night. DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.

MISSED APPROACH: Climb to 3100 direct WOSUL and hold.

AWOS-3 <b>119.075</b>	LONGVIEW APP CON* <b>128.75 379.15</b>	UNICOM <b>122.7 (CTAF) ①</b>
--------------------------	---	---------------------------------



CATEGORY	A	B	C	D
LPV DA	915-1	250 (300-1)		NA
LNAV/VNAV DA	915-1	250 (300-1)		NA
LNAV MDA	1220-1	555 (600-1)	1220-1½ 555 (600-1½)	NA
CIRCLING	1220-1	542 (600-1)	1280-1¾ 602 (700-1¾)	NA

SC-5, 11 JUL 2024 to 08 AUG 2024

SC-5, 11 JUL 2024 to 08 AUG 2024