RNAV (GPS) RWY 7L

KENOSHA RGNL (ENW)

WAAS CH 50314 W07A	APP CRS 066°	Rwy Idg 6600 TDZE 742 Apt Elev 742

RNP APCH - GPS.

Circling Rwy 7R, 15 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS, increase LNAV Cat C/D visibility to 1⅛ SM.

MALSR

MISSED APPROACH: Climb to 2500 then climbing left turn to 3000 direct DIKHU and hold.

ATIS	MILWAUKEE APP CON	KENOSHA TOWER ★	GND CON	CLNC DEL	CLNC DEL
127.175	135.875 317.725	118.6 (CTAF) L 353.6	121.875	121.875	118.6 (When twr closed)

UNICOM 122.95



ELEV 742 TDZE 742





CATEGORY	A	B	C	D
LPV DA	942-½ 200 (200-½)			
LNAV/VNAV DA	1181-¾ 439 (500-¾)			
LNAV MDA	1160-½ 418 (500-½)		1160-¾ 418 (500-¾)	
C CIRCLING	1200-1 458 (500-1)	1340-1 598 (600-1)	1400-1¾ 658 (700-1¾)	1440-2¼ 698 (700-2¼)

MIRL Rwy 7R-25L L
HIRL Rwys 7L-25R and 15-33 L
REIL Rwy 25R L

EC-3, 08 AUG 2024 to 05 SEP 2024
EC-3, 08 AUG 2024 to 05 SEP 2024