


# OZARK EIGHT DEPARTURE

AL-5316 (FAA)

ST LOUIS DOWNTOWN (CPS)  
CAHOKIA/ST. LOUIS, ILLINOIS

ATIS 121.45  
 CLNC DEL 118.275  
 121.8 (when tower closed)  
 GND CON 121.8  
 DOWNTOWN TOWER\* 119.925 379.3  
 ST LOUIS DEP CON 123.7 371.875




HALLSVILLE  
 114.2 HLY  
 Chan 89

ST. LOUIS  
 117.4 STL  
 Chan 121

8000  
 \*2500  
 281°  
 (46)

CABIT  
 8000  
 \*2100  
 281°  
 (32)



**TOP ALTITUDE:**  
 2500

NOTE: DME and RADAR required.

**TAKEOFF MINIMUMS**

Rwys 12L/R, 23, 30R: Standard.  
 Rwy 5: 200-1/4 or standard with minimum climb of 343' per NM to 700.  
 Rwy 30L: 400-2 1/2 or standard with minimum climb of 220' per NM to 900, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 2100' prior to DER.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

# OZARK EIGHT DEPARTURE

CAHOKIA/ST. LOUIS, ILLINOIS  
ST LOUIS DOWNTOWN (CPS)