

WAAS CH 58112 W05A	APP CRS 050°	Rwy Idg TDZE 123 Apt Elev 125	5001
--	------------------------	---	-------------

RNAV (GPS) RWY 5


BARTOW EXEC (BOW)

RNP APCH.

⚠ Rwy 5 helicopter visibility reduction below ¼ SM NA. When local altimeter setting not received, use Tampa Intl altimeter setting and increase LPV DA to 553 feet, LNAV/VNAV DA to 684 feet and all MDA 120 feet, increase LNAV Cat C visibility ¼ SM, Cat D ½ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C or above 54°C. VDP and Baro-VNAV NA when using Tampa Intl altimeter setting.


MISSED APPROACH:
Climb to 2300 direct ZOMOV and hold.

AWOS-3 123.775	TAMPA APP CON 120.65 290.3	BARTOW TOWER ★ 121.20 (CTAF)	GND CON 121.9	UNICOM 122.95
--------------------------	--------------------------------------	---	-------------------------	-------------------------



SE-3, 05 SEP 2024 to 03 OCT 2024

SE-3, 05 SEP 2024 to 03 OCT 2024



ELEV 125	TDZE 123
----------	----------

TWR 194

5000 X 150
4416 X 150
271 X 100
271 X 100

0.5% UP

CATEGORY	A	B	C	D
LPV DA	447-1¼		324 (400-1¼)	
LNAV/VNAV DA	509-1½		386 (400-1½)	
LNAV MDA	520-1 397 (400-1)		520-1½ 397 (400-1½)	520-1¼ 397 (400-1¼)

MIRL Rwy 5-23 and 9L-27R
REIL Rwy 5, 23, 9L and 27R