


MAYNR TWO DEPARTURE (RNAV)

SE-3, 05 SEP 2024 to 03 OCT 2024

MIAMI DEP CON
125.5 354.1
AWOS-3
118.375
CTAF
122.8

RNAV 1 - DME/DME/IRU or GPS.
From SLPJT to MAXIM: RNAV 1 - GPS.
From SLPJT to CANOA: RNAV 1 - GPS.
RADAR required.


TOP ALTITUDE:
ASSIGNED BY ATC



TAKEOFF MINIMUMS

- Rwy 10: Standard with minimum climb of 500'/NM to 2400.
- Rwy 18: Standard with minimum climb of 500'/NM to 1800.
- Rwy 28: Standard with minimum climb of 500'/NM to 1900.
- Rwy 36: Standard with minimum climb of 500'/NM to 2200.

NOTE: Jet aircraft only.
NOTE: Accelerate to 250K until leaving 10000, if unable, advise ATC.



AUSTI
5000

202°

(26)

MAYNR

191°

(27)

MCLAW

243°

(28)

*13000

*15800

FL180

*1300

265°

(36)

SLPJT

FL180

*1300

275°

(41)

JABOX

*1300

232°

(15)

FL180

*1300

261°

(41)

FL180

*1300

261°

(41)

FL180

*1300

261°

(41)

FL180

*1300

FL180

*1300

185°

(34)

FUNDI

*1300

232°

(15)

FL180

*1300

261°

(41)

FL180

*1300

261°

(41)

FL180

*1300

261°

(41)

FL180

*1300

261°

(41)

FL180

*1300

261°

(41)

FL180

*1300

261°

(41)

FL180

*1300

(CONTINUED ON FOLLOWING PAGE)

SE-3, 05 SEP 2024 to 03 OCT 2024

NOTE: Chart not to scale.

MAYNR TWO DEPARTURE (RNAV)