

RADAR MINS

23110

N1

RADAR INSTRUMENT APPROACH MINIMUMS

BISMARCK, ND

Amdt 3C, 02DEC21 (21336) (FAA)

ELEV 1661

BISMARCK MUNI (BIS)

RADAR-1 126.3 298.9 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	31		AB D	2100/24 2100/50	454 454	(500-½) (500-1)	C	2100/40	454	(500-¾)
	13		AB D	2100-1 2100-1½	445 445	(500-1) (500-1½)	C	2100-1¼	445	(500-1¼)
	21		AB	2160-1	499	(500-1)	CD	2160-1¾	499	(500-1¾)
	3		AB	2220-1	559	(600-1)	CD	2220-1¾	559	(600-1¾)
CIR	ALL RWY		AB D	2220-1 2460-2½	559 799	(600-1) (800-2½)	C	2460-2¼	799	(800-2¼)

Inoperative table does not apply to ALS Rwy 13.

DULUTH, MN

Orig-A, 30JAN20 (21112) (FAA)

ELEV 1428

DULUTH INTL (DLH)

RADAR-1 125.45 233.7 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	3		AB	1820-1	400	(400-1)	CDE	1820-1¾	400	(400-1¾)
	9		ABCDE	1820/40	392	(400-¾)				
	21		AB	1840-1	420	(500-1)	CDE	1840-1¾	420	(500-1¾)
	27		AB	1880/40	459	(500-¾)	CDE	1880/45	459	(500-¾)
C CIR	ALL RWY		A C	1880-1 1940-1½	452 512	(500-1) (600-1½)	B DE	1900-1 2400-3	472 972	(500-1) (1000-3)

Circling NA for CAT E SE of Rwys 3 and 27.

Rwy 3, 9, 21 helicopter visibility reduction below ¾ SM not authorized.

VGSI and descent angles not coincident.

For inoperative ALS, increase ASR S-09 Cats A/B visibility to RVR 5500, Cats C/D/E to 1¾ SM.

For inoperative ALS, increase ASR S-27 Cats A/B visibility to RVR 5500, Cats C/D/E to 1¾ SM.

05 SEP 2024 to 03 OCT 2024

05 SEP 2024 to 03 OCT 2024

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

23110

N1

NC-1

RADAR MINS

23110

N2

RADAR INSTRUMENT APPROACH MINIMUMS

MANDAN, ND

Amdt 5A, 18AUG16 (21224) (FAA)

ELEV 1994

MANDAN RGNL/LAWLER FLD (Y19)

RADAR-1 126.3 298.9 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	31		AB	2440-1	499	(500-1)	CD	2440-1 ³ / ₈	499	(500-1 ³ / ₈)
	13		AB	2460-1	522	(600-1)	CD	2460-1 ¹ / ₂	522	(600-1 ¹ / ₂)
CIR	ALL RWY		AB	2460-1	516	(600-1)	C	2460-1 ¹ / ₂	516	(600-1 ¹ / ₂)
			D	2560-2	616	(700-2)				

ASR S-13: Helicopter visibility reduction below 3/4 SM not authorized.

ASR S-31: Helicopter visibility reduction below 3/4 SM not authorized.

When BIS control tower closed, ASR NA.

When local altimeter setting not received, use Bismarck altimeter setting and increase all MDA 60 feet, increase all CAT C/D visibility 1/4 mile.

Circling to Rwys 4 and 22 NA.

ROCHESTER, MN

Amdt 9, 20APR23 (23110) (FAA)

ELEV 1317

ROCHESTER INTL (RST)

RADAR-1 119.8 251.125 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	13		AB	1660/24	380	(400-1/2)	CD	1660/35	380	(400-3/8)
	31		AB	1680/24	376	(400-1/2)	CD	1680/35	376	(400-5/8)
	3		ABCD	1680-1	363	(400-1)				
	21		ABCD	1680-1	375	(400-1)				
CIR	ALL RWY		A	1720-1	403	(500-1)	B	1780-1	463	(500-1)
			C	1900-1 ¹ / ₂	583	(600-1 ¹ / ₂)				

When control tower closed, procedure NA.

For nonoperative ALS increase S-13 and S-31 CATs C and D visibility to RVR 5500.

05 SEP 2024 to 03 OCT 2024

05 SEP 2024 to 03 OCT 2024

NC-1

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

23110

N2

RADAR MINS

23110

N3


RADAR INSTRUMENT APPROACH MINIMUMS

SIOUX FALLS, SD

Amdt 10B, 06FEB14 (22251) (FAA)

ELEV 1430

JOE FOSS FLD (FSD)

RADAR-1 125.8 306.2 

			DA/ MDA-VIS	HAT/ HAA	CEIL-VIS	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS	
ASR	RWY	GP/TCH/RPI	AB	1920-1	498	(500-1)	CDE	1920-1 ³ / ₈	498	(500-1 ³ / ₈)
	33		AB	1940/24	516	(600- ¹ / ₂)	CDE	1940/55	516	(600-1 ¹ / ₄)
	3		AB	1960/24	530	(600- ¹ / ₂)	CDE	1960/55	530	(600-1 ¹ / ₄)
	21		AB	1960-1	531	(600-1)	CDE	1960-1 ¹ / ₂	531	(600-1 ¹ / ₂)
CIR	ALL RWY		AB	1980-1	550	(600-1)	C	1980-1 ¹ / ₂	550	(600-1 ¹ / ₂)
			D	2040-2	610	(700-2)	E	2300-3	870	(900-3)

When control tower closed, ASR NA.

Rwy 15/33 helicopter visibility reduction below ³/₄ SM not authorized.

For inoperative MALSR, increase S-3 Cat C/D/E visibility to 1³/₈ mile.

For inoperative MALSR, increase S-21 Cat C/D/E visibility to 1¹/₂ mile.

05 SEP 2024 to 03 OCT 2024

05 SEP 2024 to 03 OCT 2024

NC-1

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

23110

N3