


LOC I-BGE 111.35	APP CRS 274°	Rwy Idg 5502
		TDZE 134
		Apt Elev 141


ILS or LOC RWY 27

DECATUR COUNTY INDUSTRIAL AIR PARK (BGE)



NA ADF required. When local altimeter setting not received, use Tallahassee Intl altimeter setting and increase S-ILS 27 DA to 429 feet and all MDA 100 feet; increase S-LOC 27 visibility Cat C, D ¼ SM and Circling Cat C, D visibility ½ SM. For inop MALS/R, when using Tallahassee Intl altimeter setting increase S-ILS 27 all Cats visibility to 1 mile.

MALS/R  MISSED APPROACH: Climb to 1200 then climbing right turn to 1900 direct LYZ NDB and hold.

AWOS-3PT 121.125	TALLAHASSEE APP CON* 128.7 254.3	CLNC DEL 124.775 335.65	UNICOM 122.975 (CTAF)
----------------------------	--	-----------------------------------	---------------------------------



ELEV 141	TDZE 134
----------	----------



CATEGORY	A	B	C	D
S-ILS 27	334-½		200 (200-½)	
S-LOC 27	480-½		346 (400-½)	
			480-¾ 346 (400-¾)	
CIRCLING	600-1 459 (500-1)		800-1¾ 659 (700-1¾)	
			860-2¼ 719 (800-2¼)	

SE-4, 03 OCT 2024 to 31 OCT 2024

SE-4, 03 OCT 2024 to 31 OCT 2024