

HIAKA ONE DEPARTURE (RNAV)

AL-762 (FAA)

PAC, 31 OCT 2024 to 26 DEC 2024

TOP ALTITUDE:
16000

NOTE: RNAV 1.
NOTE: RADAR required.
NOTE: GPS required.

NOTE: Turbopjet and turboprop aircraft only.

NOTE: APACK departures expect direct/vectors to APACK/R463.

NOTE: CANON departures expect direct/vectors to CANON.

NOTE: CARRP departures expect direct/vectors to CARRP/A579.

NOTE: CHOKO departures expect direct/vectors to CHOKO.

NOTE: CLUTS departures expect direct/vectors to CLUTS/R465.

NOTE: DAINNO departures expect direct/vectors to DAINNO.

NOTE: DOVRR departures expect direct/vectors to DOVRR/B596.

NOTE: EBBER departures expect direct/vectors to EBBER/R577.

NOTE: JULIE departures expect direct/vectors to JULIE.

NOTE: KOA departures expect direct/vectors to KOA VORTAC.

NOTE: LILIA departures expect direct/vectors to LILIA.

NOTE: NONNI departures expect direct/vectors to NONNI.

NOTE: PUPPI departures expect direct/vectors to PUPPI.

NOTE: SAKKI departures expect direct/vectors to SAKKI.

NOTE: SCOON departures expect direct/vectors to SCOON.

THOMA ◆

DAINNO ◆

▲ CANON

▲ LILIA

▲ SYVAD △ PUPPI

NONNI ▲



◆ CHOKO

JULIE △ SAKKI

UPOLO POINT ◆
UPP

◆ KONA
KOA

▲ CARRP

▲ DOVRR

◆ TARDE

TAKEOFF MINIMUMS
Rwy 2: Standard with minimum climb of 500' per NM to 554.
Rwys 5, 20, 23: NA - ATC.
NOTE: Chart not to scale.


▲ APACK

▲ CLUTS

ROSAH
1600

EBBER ▲

ATS
128.6
CLINC DEL
120.6, 290.5
GND CON
121.9, 279.6
MAUI TOWER*
118.7, 279.6
HCF APPROACH
NORTH 120.2, 322.4
SOUTH 119.5, 225.4



SCOON ▲

▼ DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 2: Climb heading 024° to 554, then direct HIAKA, thence. . . .
. . . on track 024° to cross ROSAH at or above 1600, then on track 024° for RADAR vectors to assigned route/fix, maintain 16000 or as assigned by ATC. Expect clearance to filed altitude/flight level within 10 minutes after departure.

HIAKA ONE DEPARTURE (RNAV)

PAC, 31 OCT 2024 to 26 DEC 2024