ILS or LOC RWY 35

ACADIANA RGNL (ARA)

LOC/DME I-ARA	APP CRS	Rwy Idg	8002
108.9	348°	TDZE	21
Chan 26		Apt Elev	24

DME required for procedure entry. DME required for LOC only.

Circling NA to Rwys 17W and 35W. For inop ALS increase S-ILS 35 Cat E visibility to ¾ SM and S-LOC 35 Cats C/D/E visibility to 1⅛ SM.

MALSR

MISSED APPROACH: Climb to 800 then climbing right turn to 2000 on heading 080° and LFT R-114 to CLYNT INT/LFT 18.8 DME and hold.

ASOS	LAFAYETTE APP CON ★	ACADIANA TOWER ★	GND CON	CLNC DEL	CLNC DEL	UNICOM	
133.325	121.1 268.7	125.0 (CTAF) L 239.3	121.7	121.7	118.05 (when twr closed)	122.95	122.7 L

LAFAYETTE 109.8 LFT Chan 35

Procedure NA for arrival on LFT VORTAC airway radials 092 CW 114.

3000 to PILYI 156° (24.4)

LOCALIZER 108.9 I-ARA Chan 26

1049 LULEW LSU 27.7

116.5 LSU Chan 112

511 R-114 R-211

CLYNT LFT 18.8

294° 114°

604 297 131 283 533 221

119± UXYAP I-ARA 4

139

463

ISUCE I-ARA 6.7

324

MSA LFT 25 NM 180° 2900 2100 360°

348° 1700 (8)

(IF/IAF) PILYI I-ARA 14.7 LFT 24.4

168° 348° 1 min 168°

HOLD 4500 2000

ALTERNATE MISSED APCH FIX

116.5 LSU Chan 112

LULEW LSU 27.7

221° 041° R-221

ELEV 24 D TDZE 21

HIRL Rwy 17-35 L

Seaway Rwy 17W-35W L

17 35W 8002 X 200 5000 X 150 TWR 103 105 35 348°

800	2000	LFT	CLYNT
	hdg 080°	R-114	△

*LOC only.

I-ARA 1.6 *I-ARA 2.6 UXYAP I-ARA 4 ISUCE I-ARA 6.7 1700 348° 480* 1700

PILYI I-ARA 14.7 One Minute Holding Pattern 168° 348° 4500 2000

GS 3.00° TCH 51

1 NM 1.4 NM 2.7 NM 8 NM

CATEGORY	A	B	C	D	E
S-ILS 35	221-½ 200 (200-½)				
S-LOC 35	440-½ 419 (500-½)		440-¾ 419 (500-¾)		
C CIRCLING	440-1 416 (500-1)	480-1 456 (500-1)	600-1½ 576 (600-1½)	680-2 656 (700-2)	900-3 876 (900-3)

SC-4, 31 OCT 2024 to 28 NOV 2024

SC-4, 31 OCT 2024 to 28 NOV 2024