LOC/DME I-RDM	APP CRS	Rwy Idg	7031
109.1	226°	TDZE	3067
Chan 28		Apt Elev	3082

ILS or LOC RWY 23

ROBERTS FLD (RDM)

DME required.

T A -17°C

Autopilot coupled approach NA below 4370. When local altimeter setting not received, use Bend altimeter setting increase S-ILS 23 DA to 3348 feet; increase all MDAs 100 feet increase S-LOC 23 Cat C/D/E visibility ⅜ SM and Circling Cats C/D/E visibility ½ SM. For inop ALS, increase S-ILS 23 Cat E visibility to ¾ SM and S-LOC 23 Cat C/D/E visibility to 1 SM. For inop ALS when using Bend altimeter setting increase S-ILS 23 all Cats visibility to ⅞ SM and increase S-LOC 23 Cats C/D/E visibility to 1⅜ SM. VDP NA when using Bend altimeter setting.

MALSR

MISSED APPROACH: Climb to 3700 then climbing right turn to 7000 on heading 320° and DSD VORTAC R-348 to CUPRI/DSD 22 DME and hold.

ATIS	SEATTLE CENTER	REDMOND TOWER*	GND CON	UNICOM
119.025	126.15 269.475	124.5 (CTAF) L 256.8	121.8	122.95



ELEV 3082 D TDZ 3067





CATEGORY	A	B	C	D	E
S-ILS 23	3267-½ 200 (200-½)				
S-LOC 23	3440-½ 373 (400-½)		3440-⅝ 373 (400-⅝)		
C CIRCLING	3540-1 458 (500-1)	3560-1 478 (500-1)	3640-1½ 558 (600-1½)	3740-2 658 (700-2)	3820-2½ 738 (800-2½)

REIL Rwys 5, 11, and 29 L
HIRL Rwy 5-23 L
MIRL Rwy 11-29 L

NW-1, 28 NOV 2024 to 26 DEC 2024
NW-1, 28 NOV 2024 to 26 DEC 2024