METRO FOUR DEPARTURE

(METRO4.DXO) 05SEP24

OAKLAND COUNTY INTL (PTIK)

PONTIAC, MICHIGAN

(METRO4.DXO) 24249

METRO FOUR DEPARTURE

AL-5052 (FAA)

OAKLAND COUNTY INTL (PTIK)

PONTIAC, MICHIGAN

ATIS 125.025
CLNC DEL 118.25
GND CON 121.9
PONTIAC TOWER ★
120.5 (CTAF)

RADAR required. DME required.

TOP ALTITUDE: 3000

TAKEOFF MINIMUMS

Rwys 18, 36: NA - Environmental.

Rwys 9L/R, 27L/R: Standard.

NOTE: For use by non-RNAV equipped aircraft only.

NOTE: When using this departure, file the appropriate depicted departure fix and route. Aircraft over HARWL must file FL220 and below. Aircraft landing Cleveland (CLE) must file MAARS transition. Turbojet departures at/above 10000, maintain 280K until advised by ATC. If unable, advise ATC prior to departure.

SPECIAL INSTRUCTIONS:

For appropriate departure control frequency, see graphic. Use frequency depicted within the sector where first navaid/fix for your route is located (sectors indicated by dashed lines; frequencies in dashed box within).



NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)