

APP CRS

Rwy Idg

6300

TDZE

6431

Apt Elev

6451

RNAV (RNP) Z RWY 1

JACKSON HOLE (JAC)

RNP APCH

▼

-22°C

For uncompensated Baro-VNAV systems, procedure NA below -27°C or above 54°C.
Inop table does not apply to RNP 0.11* all Cats visibility.
For inop ALS, increase RNP 0.30* all Cats visibility to ¾ SM.
Missed approach requires RNP less than 1.0.

MALS

MISSED APPROACH: Climb to 14000 on track 007° to UBEVE and track 007° to QUIRT and track 088° to DNW VOR/DME and hold, continue climb-in-hold to 14000.
* Missed approach requires minimum climb of 330 feet per NM to 8200; if unable to meet climb gradient, see RNAV (RNP) Y RWY 1.

D-ATIS	SALT LAKE CENTER	JACKSON TOWER*	GND CON	UNICOM
120.625	133.25 285.6	118.075 (CTAF)	124.55	122.95

VUGUY	LYET	NECPI	UBEVE	QUIRT	DNW
14000	11600	11200	10500	9900	8600
GP 3.00°					
TCH 50					
	12 NM	2 NM	2.4	2.4	7.9 NM
					6.7 NM
CATEGORY	A	B	C	D	
RNP 0.11 DA*		6690-¾	259 (300-¾)		
RNP 0.30 DA*		6743-¾	312 (300-¾)		

AUTHORIZATION REQUIRED

ELEV 6451

TDZE 6431

CL Rwy 1-19

HIRL Rwy 1-19

TWR 6506

6300 X 130

0.65% UP

006°

JACKSON, WYOMING

Amcl 1 13SEP18

43°36'N-110°44'W

JACKSON HOLE (JAC)

RNAV (RNP) Z RWY 1