

WAAS
CH **77623**
W30A

APP CRS
301°

Rwy Idg
TDZE
Apt Elev
5635
295
295

RNAV (GPS) RWY 30

VISALIA MUNI (VIS)

RNP APCH.

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM, LNAV Cats C/D to 1 SM.

MALSR

AS

MISSED APPROACH: Climb to 3000 direct INOC1 and on track 267° to LATON and hold, continue climb-in-hold to 3000.

AWOS-3PT 119.925	FRESNO APP CON 118.5	CLNC DEL 118.5	UNICOM 123.05 (CTAF) 0
----------------------------	--------------------------------	--------------------------	----------------------------------

ELEV 295

D

TDZE 295

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

3000

INOC1

LATON

*LNAV only.

HOTU1.5 NM to RW30

PACOD

PANES

4 NM Holding Pattern

GP 3.00°

TCH 53

1 NM

0.5 NM

3.7 NM

5.9 NM

CATEGORY	A	B	C	D
LPV DA	502-½ 207 (300-½)			
LNAV/VNAV DA	554-½ 259 (300-½)			
LNAV MDA	660-½ 365 (400-½)		660-⅝ 365 (400-⅝)	
CIRCLING	720-1 425 (500-1)	760-1 465 (500-1)	760-1½ 465 (500-1½)	940-2 645 (700-2)

VISALIA, CALIFORNIA

Amcl 2 15AUG19

36°19'N-119°24'W

VISALIA MUNI (VIS)

RNAV (GPS) RWY 30