

APP CRS
309°

Rwy Idg
TDZE
Apt Elev

4499
1715
1723

RNAV (GPS) RWY 31

CHAUTAUQUA COUNTY/JAMESTOWN (JHW)

RNP APCH-GPS

▼

NA


Rwy 31 Straight-in/Circling and Circling to Rwy 13 NA at night.
When local altimeter setting not received, use Dunkirk altimeter setting:
increase all MDAs 200 feet and visibility LNAV Cats C/D ¾ SM, Circling Cat C ½ SM
and Circling Cat D ¾ SM. Helicopter visibility reduction below 1 SM NA.

MISSED APPROACH: Climb
to 4000 direct CRYST WP
and hold.

AWOS-3PT
118.425

BUFFALO APP CON ★
126.05

UNICOM
122.975 (CTAF) 0



ELEV 1723

D

TDZE 1715

REIL Rwy 31 0

MIRL Rwy 13-31 0

HIRL Rwy 7-25 0

4000

CRYST

FOXAT 3 NM to FELMO

GOSPL

4 NM Holding Pattern

129°

309°

4000

RW31

FELMO

3400

3800

3.10°

TCH 50

5 NM

3 NM

2 NM

CATEGORY	A	B	C	D
LNAV MDA	2200-1	485 (500-1)	2200-1¼ 485 (500-1¼)	2200-1½ 485 (500-1½)
CIRCLING	2200-1	477 (500-1)	2260-1½ 537 (600-1½)	2340-2 617 (700-2)