



VOR/DME HRL	APP CRS	Rwy Idg	9400
113.65	160°	TDZE	35
Chan 83 (Y)		Apt Elev	36

VOR RWY 18R
VALLEY INTL (HRL)

DME required. For inop ALS, increase S-18R Cat C/D visibility to 1 3/8 SM. When local altimeter setting not received, use Port Isabel altimeter setting and increase all MDAs 60 feet and S-18R visibility Cat C/D to RVR 5500 and Circling visibility Cat C/D 1/4 SM. VPD NA when using Port Isabel altimeter setting.	MALSR AG	MISSED APPROACH: Climb to 1200 then climbing right turn to 2000 direct HRL VOR/DME and hold, continue to climb in hold to 2000.
--	-------------	---

ATIS 124.85	VALLEY APP CON 120.7 279.5	HARLINGEN TOWER ★ 119.3 (CTAF) 317.6	GND CON 121.7	UNICOM 122.95
----------------	-------------------------------	---	------------------	------------------



CATEGORY	A	B	C	D
S-18R	440/24	405 (500-1/2)	440/40	405 (500-3/4)
CIRCLING	460-1 424 (500-1)	560-1 524 (600-1)	600-1 1/2 564 (600-1/2)	680-2 644 (700-2)

