

WAAS CH 56430 W06A	APP CRS 058°	Rwy Idg 6006 TDZE 186 Apt Elev 213
--	------------------------	---

RNAV (GPS) Z RWY 6

TRENTON MERCER (TTN)


RNP APCH - GPS.

Baro-VNAV and VDP NA when using Northeast Philadelphia altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C or above 54°C. When local altimeter setting not received, use Northeast Philadelphia altimeter setting and increase LPV DA to 437 feet; increase LNAV/VNAV DA to 658 feet and all visibilities ¼ SM; increase all MDAs 60 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C ¼ SM. For inop ALS, increase LNAV visibility Cats C/D to 1 ¾. For inop ALS when using Northeast Philadelphia altimeter setting, increase LNAV/VNAV all Cats visibility to 1 ¾ and LNAV visibility Cats C/D to 1 ¾. When Circling to Rwy 34 at night, operational VGSI required, remain on or above VGSI glidepath until threshold.

MALSR

MISSED APPROACH:
Climb to 1500 then climbing left turn to 2700 direct ZUBAX and hold.

ATIS 126.775	PHILADELPHIA APP CON 123.8 291.7	TRENTON TOWER ★ 120.7 (CTAF) 0 257.8	GND CON 121.9 257.8	CLNC DEL 121.9 257.8	UNICOM 122.95
------------------------	--	--	-------------------------------	--------------------------------	-------------------------



ELEV 213

D

TDZE 186

4 NM Holding Pattern

ZUBAX

COPIX

GP 3.00° TCH 60

2700

238°

058°

058°

1900

1900

2700

001° (8.2)

4 NM (IAF) MENGE

EMUNY 2 NM to RWY 06

1.5 NM to RWY 06

0.5 NM

1.5 NM

* LNAV only.

* 840

1500

2700

ZUBAX

GP 3.00° TCH 60

2700

238°

058°

058°

1900

1900

2700

001° (8.2)

4 NM (IAF) MENGE

EMUNY 2 NM to RWY 06

1.5 NM to RWY 06

0.5 NM

1.5 NM

* LNAV only.

* 840

1500

2700

ZUBAX

CATEGORY	A	B	C	D
LPV DA		390-1½	204 (200-1½)	
LNAV/VNAV DA		611-¾	425 (400-¾)	
LNAV MDA	700-1½	514 (500-1½)	700-1	514 (500-1)
CIRCLING	700-1	487 (500-1)	760-1½ 547 (600-1½)	960-2½ 747 (800-2½)

HIRL Rwy 6-24 and 16-34 1
REIL Rwy 16, 24 and 34 1