

WAAS CH 78032 W18A	APP CRS 181°	Rwy Idg 4098 TDZE 573 Apt Elev 573
--	------------------------	---

RNAV (GPS) RWY 18


SALEM-LECKRONE (SLO)

⚠

Baro-VNAV NA when using Centralia altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C (-5°F) or above 54°C (130°F). When local altimeter setting not received, use Centralia altimeter setting: increase LPV DA to 801 feet; increase LNAV/VNAV DA to 890 feet and visibility 1⁄8 SM; increase all MDAs 40 feet and LNAV Cats C/D visibility 1⁄8 SM and Circling Cats C/D visibility 1⁄4 SM. DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 2600 direct EMLJ and hold.

AWOS-3PT 118.525	KANSAS CITY CENTER 127.7 351.825	UNICOM 122.725 (CTAF) 0
----------------------------	--	--



MISSED APCH FIX EMLJ		ELEV 573		TDZE 573	
2600		EMLJ		181°	
*LNAV Only		JEGUS 2200		EDHUJ 4 NM Holding Pattern	
RW18 1.5 NM to RW18		RW18 1.6 NM to RW18		001° → 2600	
1.5 NM		0.1 NM		3.4 NM	
7 NM		2200		GP 3.00° TCH 40	
CATEGORY	A	B	C	D	
LPV DA	773-1		200 (200-1)		
LNAV/VNAV DA	862-1		289 (300-1)		
LNAV MDA	940-1		367 (400-1)		
CIRCLING	1040-1 467 (500-1)		1380-2¼ 807 (900-2¼)		1380-2½ 807 (900-2½)
SALEM, ILLINOIS		REIL Rwy 18-36		MIRL Rwy 18-36	